

113073

BOOK 7/6 PAGE 77

LAND CORNER RECORD

(THIS FORM PRESCRIBED BY THE PUBLIC LAND SURVEY OFFICE, DEPARTMENT OF NATURAL RESOURCES, PURSUANT TO RCV 58.09. ALPHA-NUMERIC INDEX DIAGRAM ON THE BACK.)

CORNER INDEXING INFORMATION:

TWP 7 N RGE 6 E CORNER CODE T-21
(Willamette Meridian) (See Instructions on back of LCR)

ADDITIONAL IDENTIFIER: (e.g., BLM designation for the corner, street intersection, plat name, block, lot, etc.)

East quarter corner Section 25

COUNTY: Skamania

AUDITOR'S USE


LAND SURVEYOR INFORMATION: (or Public Officer as per RCV 58.09.090)

This corner record correctly represents work performed by me or under my direction in conformance with the Survey Recording Act.

COMPANY OR AGENCY: Hagedorn, Inc.

ADDRESS: 1924 Broadway, Suite B
Vancouver, WA 98663FILED FOR RECORD
SKAMANIA CO. WASH.
BY Hagedorn, Inc.

MAR 11 10 0 AM '92

P. Darrow
FOR
GARY K. OLSON

SEAL / SIGNATURE/DATE

3-6-92

WASHINGTON PLANE COORDINATES: N:

E:

ORDER:

ZONE:

DATUM (Date of adjustment):

CORNER INFORMATION: Use the space below to provide the following information regarding the corner:
(1) Pertinent Corner History, **(2) Evidence Found at the Corner,** and **(3) Corner Perpetuation Information.** Please title and number the parts of your discussion accordingly. If additional space is needed use the back. (For (3), diagram the references. Also, provide the cross-reference to a map of record, if applicable, the surveyor's field book no./page no., and the date of work.) (See the back of this form for the requirements of the Survey Recording Act.)

(1) Pertinent Corner History:

"Quarter Section Post" originally set by Lewis D.W. Shelton, U.S. Deputy Surveyor, under Contract No. 552 in 1900, from which:

12" fir, South 42° 45' East, 68 links
9" fir, North 11° 45' West, 12.5 links


(2) Evidence Found at the Corner:

We visited this corner in January 1992 while doing a survey for Leonard Hollenbeck and found the DNR monument noted below. Reference trees were found intact with grown over scribed faces. No new reference trees were added due to proximity of corner to campground, cabin, etc.

(3) Corner Perpetuation Information:

The following data is from the DNR "setting of concrete monument" form. We are filing this data on a land corner record to make it available to the public record.

STATE OF WASHINGTON
DEPARTMENT OF NATURAL RESOURCES
SETTING OF CONCRETE MONUMENT



Corner: 1/4 corner common to Sections 25 and 26, T7N, R6E, W.M.

Date: September 1, 1968

By: Morris Engineering

Date: R.M. Morris, McMinnville, Oregon, set the above corner in compliance with a D.N.R. purchaser's survey. He found a dead 9" snag with scribing in the West quadrant.

Morris set a standard D.N.R. concrete monument from which:

A fir, 10" bears S 160 W, 32 ft., marked 1/4 S 26 BT
A fir, 18" bears N 70° E, 9 ft., marked 1/4 S 25 BT

Registered
Indexed, Dir
Indirect
Filmed 3/13/92
Mailed

DATE OF FORM: 2/92

(Signed) P. Darrow

MARK THE CORNER LOCATION ON THE DIAGRAM BELOW AND FILL IN THE CORNER CODE BLANK ON THE OTHER SIDE:
 (1) For corners located at the intersection of two lines (Section corners, quarter corners and sixteenth corners):

(a) The corner code is the alpha-numeric coordinate from the diagram below that corresponds to the appropriate intersection of lines.

(2) For corners that are not located at the intersection of two lines (Meander corners; DLC's, HES's, reservation boundaries, mining claims, etc.):

(a) For corners that are on one line only the corner code is the line designation and the related line segment; i.e., a corner on Line 5 between "B" and "C" is designated BC-5.

(b) For corners that are between lines the corner code is both line segments; i.e., a corner in the SE1/4 of the SE1/4 of section 18 is designated MM-4-5.

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25

A																							
B																							
C	6		5		4		3		2		1												
D																							
E																							
F																							
G	7		8		9		10		11		12												
H																							
J																							
K																							
L	18		17		16		15		14		13												
M																							
N																							
O																							
P	19		20		21		22		23		24												
Q																							
R																							
S																							
T	30		29		28		27		26		25												
U																							
V																							
W																							
X	31		32		33		34		35		36												
Y																							
Z																							

RCW 58.09.060 (2) requires the following information on this form: an accurate description and location, in reference to the corner position, of all monuments and accessories (a) found at the corner and (b) placed or replaced at the corner; (c) basis of bearings used to describe or locate such monuments or accessories; and (d) corollary information that may be helpful to relocate or identify the corner position.

SPACE FOR ADDITIONAL COMMENT: