

113741

BOOK 215 PAGE 63

FILED FOR RECORD
BY *Bob Glaeser*

JUN 16 4 07 PM '92

Gary H. Olson
GARY H. OLSON**LAND CORNER RECORD**(THIS FORM PRESCRIBED BY THE PUBLIC LAND SURVEY
OFFICE, DEPARTMENT OF NATURAL RESOURCES, PURSUANT
TO RCW 58.09. ALPHA-NUMERIC INDEX DIAGRAM ON
THE BACK.)**Corner Indexing Information:**TWP 2 North RGE 5 East Corner Code T-1
(Willamette Meridian)ADDITIONAL IDENTIFIER: (e.g., BLM designation
for the corner, street intersection, plat name,
block, lot, etc.)West quarter Corner Section 30, Township 2 North, Range 5 East,
Willamette MeridianRegistered p
Indexed, Dir p
Indexed p
Filed 6/24/92
Mailed

Skamania County Washington:

AUDITOR'S USE

Land Surveyor Information: (or Public Officer as per RCW 58.09.090)

This corner record correctly represents work performed by me or
under by direction in conformance with the Survey Recording Act.Company or agency:
Minister & Glaeser Surveying, Inc.
2208 E. Evergreen Blvd.
Vancouver, WA. 98661
(206) 694-3313Signature *Robert W. Glaeser*Date: 6-15-92 Seal: Washington Plane Coordinates: N:
Order: Zone:E:
Datum (Date of adjustment):**Corner Information:** Use the space below to provide the following
information regarding the corner.**(1) Pertinent Corner History:**The original survey was conducted by Deputy Surveyor John Trutch,
under Contract No. 24, dated February 21, 1857. The survey was
performed between April 9 and June 24, 1857. Set quarter section
post at 40 chains North of the Southwest corner to Section 30.

B.T.'s were as follows:

30" Dia. Fir Stub, N. 50° W., 69 Links
40" Dia. Fir Stub, N. 47° E., 102 Links**(2) Evidence Found at the Corner:**No original evidence found. Found 3/4" iron pipe with brass cap
along with R.P.'s as found in Skamania County Survey, Book 1,
Page 196. The 3/4" iron pipe with brass cap was accepted as the
corner based on reputation and use.

(3) Corner Perpetuation Information:
Corner is shown on the following Clark County Maps
of Record.

Surveys

Subdivisions

Short Plats

Unofficial
Copy

MARK THE CORNER LOCATION ON THE DIAGRAM BELOW AND FILL IN THE CORNER CODE
BLANK ON THE OTHER SIDE:

(1) For corners located at the intersection of two lines (Section corners, quarter corners and sixteenth corners):

(a) The corner code is the alpha-numeric coordinate from the diagram below that corresponds to the appropriate intersection of lines.

(2) For corners that are not located at the intersection of two lines (Meander corners, DLC's, HES's, reservation boundaries, mining claims, etc.):

(a) For corners that are on one line only the corner code is the line designation and the related line segment; i.e., a corner on line 5 between "B" and "C" is designated BC-5.

(b) For corners that are between lines the corner code is both line segments; i.e., a corner in the SE1/4 of the SE1/4 of section 18 is designated MN-4-5.

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
A																									
B																									
C			6				5				4				3				2						
D																									
E																									
F																									
G			7				8				9				10				11						
H																									
J																									
K																									
L			18				17				16				15				14						
M																									
N																									
O																									
P			19				20				21				22				23						
Q																									
R																									
S																									
T			30				29				28				27				26						
U																									
V																									
W																									
X			31				32				33				34				35						
Y																									
Z																									

RCW 58.09.060 (2) requires the following information on this form: an accurate description and location, in reference to the corner position, of all monuments and accessories (a) found at the corner and (b) placed or replaced at the corner; (c) basis of bearings used to describe or locate such monuments or accessories; and (d) corollary information that may be helpful to relocate or identify the corner position.

SPACE FOR ADDITIONAL COMMENT: