

114323


BOOK 2/6 PAGE 9

LAND CORNER RECORD

(THIS FORM PRESCRIBED BY THE PUBLIC LAND SURVEY OFFICE, DEPARTMENT OF NATURAL RESOURCES, PURSUANT TO RCW 58.09. ALPHA-NUMERIC INDEX DIAGRAM ON THE BACK.)

CORNER INDEXING INFORMATION:TWP 2N RGE 6E CORNER CODE V-17
(Willamette Meridian) (See Instructions on back of LCR)

ADDITIONAL IDENTIFIER: (e.g., BLM designation for the corner, street intersection, plat name, block, lot, etc.)


 Registered 1
 Indexed, with 1
 Indirect 1
 Filed 9/14/92
 Mailed 1
COUNTY: SKAMMIA

AUDITOR'S USE

LAND SURVEYOR INFORMATION: (or Public Officer as per RCW 58.09.090)

This corner record correctly represents work performed by me or under my direction in conformance with the Survey Recording Act.

COMPANY OR AGENCY: LACY ENGINEERING, INC.ADDRESS: 510 W. MILL PLAIN BLVD. STE 2A
VANCOUVER, WA 98660
 FILED FOR RECORD
 SKAMMIA, WASH
 BY Lacy Engineering
 SEP 1 11 58 AM '92
J. Savry
 GARY M. OLSON

SEAL/SIGNATURE/DATE

WASHINGTON PLANE COORDINATES: N:

E:

ORDER:

ZONE:

DATUM (Date of adjustment):

CORNER INFORMATION: Use the space below to provide the following information regarding the corner: (1) Pertinent Corner History, (2) Evidence Found at the Corner, and (3) Corner Perpetuation Information. Please title and number the parts of your discussion accordingly. If additional space is needed use the back. (For (3), diagram the references. Also, provide the cross-reference to a map of record, if applicable, the surveyor's field book no./page no., and the date of work.) (See the back of this form for the requirements of the Survey Recording Act.)

- (1) A) ORIGINAL CORNER SET BY VAN VLEET & NEWSOME UNDER CONTRACT NO. 47
 DATED 23rd APRIL 1860. SET A POST FROM WHICH:
 A FIR 60in. DIA. BEARS N 25° E 10 LKS. DIST.
 A FIR 66in. DIA. BEARS N 20° W 23 LKS. DIST.
 A FIR 18in. DIA. BEARS S 71° W 42 LKS. DIST.
 AN ALDER 6in. DIA. BEARS S 62° E 70 LKS. DIST.
- B) THE BONNEVILLE POWER ADMINISTRATION ON A RIGHT-OF-WAY PLAT FOR THE
 MILE 5 BONNEVILLE-VANCOUVER TRANSMISSION LINE DATED JULY 22, 1941
 SHOWS A 6" x 6" x 10" ROCK AND HUB IN E-W & S FENCE INTERSECTION
 AT THE CORNER LOCATION.
- C) IN JULY 1962, MARK & CHASE UNDER THE DIRECTION OF CLARK H. ELDRIDGE,
 R.L.S. SHOW A STONE W/X AT THE CORNER LOCATION ON THEIR PLAT OF
 WOODWARD MARINA ESTATES. RECORDED IN VOL. A OF PLATS, PAGE 44.
- D) OLSON ENGINEERING ON A RECORD OF SURVEY DATED FEBRUARY 1974 AND
 RECORDED IN BOOK 1, PAGE 34, SHOW THE FOLLOWING:
 FD. 2B.T.'s, 1 WITH SCRIBING
 FD. ROCK WITH X
 R.P.s 22" OAK - S 58° W 17.50' R.P.s TO R.R. SPIKE OR NAIL
 12" FIR- N 36° W 38.65' IN FACE OF TREES APPROX. 1'
 14" ALDER - N 26° E 8.00' FT. FROM BASE.
- E) ALVA W. BETTES, P.E. & L.S. NOTES FINDING A STONE SCRIBED " + "
 AT THE CORNER LOCATION ON A RECORD OF SURVEY DATED JUNE 1977,
 AND RECORDED IN BOOK 1, PAGE 128.

DATE OF FORM: 2/92

MARK THE CORNER LOCATION ON THE DIAGRAM BELOW AND FILL IN

PLANS ON THE OTHER SIDE

(1) For corners located at the intersection of two lines (Section corners, quarter corners and sixteenth corners):

(a) The corner code is the alpha-numeric coordinate from the diagram below that corresponds to the appropriate intersection of lines.

(2) For corners that are not located at the intersection of two lines (Meander corners, DLC's, HES's, reservation boundaries, mining claims, etc.):

(a) For corners that are on one line only the corner code is the line designation and the related line segment; i.e., a corner on line 5 between "B" and "C" is designated BC-5.

(b) For corners that are between lines the corner code is both line segments; i.e., a corner in the SE1/4 of the SE1/4 of section 18 is designated MM-4-5.

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
A																									
B																									
C			6			5					4				3				2				1		
D																									
E																									
F																									
G			7			8					9				10				11				12		
H																									
J																									
K																									
L			18			17					16				15				14				13		
M																									
N																									
O																									
P			19			20					21				22				23				24		
Q																									
R																									
S																									
T			30			29					28				27				26				25		
U																									
V																									
W																									
X			31			32					33				34				35				36		
Y																									
Z																									

RCV 58.09.060 (2) requires the following information on this form: an accurate description and location, in reference to the corner position, of all monuments and accessories (a) found at the corner and (b) placed or replaced at the corner; (c) basis of bearings used to describe or locate such monuments or accessories; and (d) corollary information that may be helpful to relocate or identify the corner position.

SPACE FOR ADDITIONAL COMMENT:

(2) EVIDENCE FOUND AT CORNER AUGUST 5, 1992:

NOTE: BEARINGS ARE MAGNETIC
WITH 22° E DECLINATION

FND. 23" D. FIR
N 36° W
(SET 6" SPIKE
IN FACE AT
BASE 38.0
FEET FROM
STONE WITH "+")

FND. 22" OAK STUMP
(AS NOTED BY OLSON)

FND. -66" ROTTED D. FIR STUMP
N 20° W 17.25' (TO CENTER)

FND. 19" ALDER (AS NOTED BY
N 26° E OLSON)
(SET 6" SPIKE IN FACE 7.70
FEET FROM STONE W/ "+")

FND. ROTTED R.R. TIE & FENCE
INTERSECTION AND RUSTED
STEEL FENCE POST WITH
HIGHWAY REFLECTOR AND
GREEN REFLECTIVE TAPE IN
FORM OF "X". THESE POSTS
ARE APPROXIMATELY 0.4 FEET
EAST OF STONE WITH SCRIBED "+".

(3) CORNER PERPETUATION INFORMATION