

RES 20-1808(9-77)

LAND CORNER RECORD

S13
S24

T. 10 N, R. SE, W.M. County SKAMANIA
 Segregated Surveys: Corner Code No. N-25
 Name: Corner No.:
 D.L.C. HES, Tract. Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

ESTABLISHED BY C.W. RIDDELL UNDER CONTRACT No. 628, DATED MARCH 7, 1905.

2. Description of Evidence Found:

OBT, 16" FIR BLOWDOWN, SCRIBES "10" VISIBLE ON CHOPPED-UP FACE, BEARS N43°E 7.9 FT. (12 LKS.)
 OBT, 18" FIR BLOWDOWN, CHOPPED-UP FACE, BEARS S48°E 34.0 FT. (REC. S52°E 62 LKS. = 40.9 FT.) MEASURES 40.9 FT. ON SLOPE.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. NUM C3 Page No. 10 Date of work 9-24-84

AT REC. BEAR. + DIST. FROM NE. OBT I SET A 2" x 30" AL. PDE WITH 2 1/2" AL. CAP MKD. AS SHOWN → 24" IN GROUND.

NO LIVE TREES IN AREA. I SET 2 REF. MONS. AS FOLLOWS:

5" x 30" STEEL REBAR WITH 1 1/2" AL. CAP MKD. "T10N R5E S13 RM" BEARS N 28 1/4° W, 10.82 FT.

5" x 30" STEEL REBAR WITH 1 1/2" AL. CAP MKD. "T10N R5E S24 RM" BEARS S 29 1/2° W, 16.53 FT.


T10N	T10N
S13	R6E
S24	S18
R5E	
1984	
RLS	16966

REF. MON
 N 28 1/4° W
 10.82'
 S 29 1/2° W
 16.53'
 REF. MON.

Washington Plane Coordinates: Zone, Y

Order Accuracy. Derived From:

Pin Pointed on Photo No. Date Location




Registered S
 Indexed, in S
 Indirect
 Filed
 Mailed

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date 9-30-84

Signature

Certificate No. 16966



AUDITOR'S CERTIFICATE

Filed for record this 21st day of FEBRUARY 1986 at 10:05 A.M. In Book 10/5 of MONUMENTS at page 75 at the request of VICTOR M. MC LIND

Signature of Auditor
 County Auditor