

LAND CORNER RECORD

4518

T 10 N, R 6 E, W.M. County SKAMANIA
 Segregated Surveys: Corner Code No. N-3
 Name: Corner No.:
 DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

ESTABLISHED BY C.W. PECORE AND F.G. BETTS UNDER SPECIAL INSTRUCTIONS
 DATED MARCH 20, 1914, GROUP 17.

2. Description of Evidence Found:

PORPHYRY STONE, 24"x10"x10", MKD. "4518" LYING LOOSELY ON GROUND.
 OBT, 11" FIR SNAG, FACE HAS BEEN CHOPPED OPEN, SCRIBES "18" VISIBLE, BEARS
 N 22 1/2° E 17.2 FT. (26 LRS.)
 OTHER OBT IS MISSING.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. NVM C 2 Page No. 17 Date of work 9-10-84

AT RECORD BEAR & DIST. FROM OBT I SET A 2"x30" AL. PIPE
 WITH 2 1/2" AL. CAP MKD. →
 24" IN GROUND, AND BURIED STONE MON. ALONGSIDE.

NO LIVE TREES IN AREA. I SET 2 REF. MONUMENTS AS FOLLOWS:
 5/8" x 30" STEEL REBAR WITH 1 1/2" AL. CAP MKD. "4518RM"
 BEARS N 42 1/2° E, 18.68 FT.
 5/8" x 30" STEEL REBAR WITH 1 1/2" AL. CAP MKD. "4518RM" BEARS
 N 53 1/2° W, 16.26 FT.

T10N R6E

4518

1984

RLS 16966

REF. MON

Q 453 1/2° W 16.26 FT.
 N 42 1/2° E 18.68 FT.
 REF. MON.

NOTE: THIS COR. REFERS TO SEC. 18 ONLY.

Washington Plane Coordinates: Zone, Y
 Order Accuracy. Derived From:
 Pin Pointed on Photo No. Date Located at
 Registered S
 Indexed Jir
 Indexed S
 Filed
 Mailed

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date 9-30-84
 Signature Victor M. McLind Certificate No. 16966

AUDITOR'S CERTIFICATE

Filed for record this 21st day of FEBRUARY 1986 at 10:15 A.M. In Book 10/6 of MONUMENTS at page 12 at the request of VICTOR M. MC LIND

Witnessed by J. D. New, Dep.
 County Auditor