State of Washington DEPARTMENT OF NATURAL RESOURCES

BUREAU OF SURVEYS AND MAPS LAND CORNER RECORD

<u>33</u>

Skamania County

T 6 N, R 5 E, W.M.

Corner Code No. Z-11

Segregated Surveys:

Name: n/a

Corner Number: n/a

1. History of Corner Establishment and Subsequent Restoration:

Originally established in 1909 by GLO surveyor C. Frank Rhodes with a marked stone and 1 dead BT and 1 live BT.

No subsequent restoration found.

FILES FOR RECORD SKAMA WASH

2. Description of Evidence Found:

Original stone marked 1/4 (closed four). 26" BT stub at N81E 56 feet.

30" BT stub S45E 26.4 feet.

36" fir line tree at west, 265 feet. 36" fir line tree at west, 392 feet.

28 PH 18

d Their dy. AUDITOR GARY M. OLSON

Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 601.07, Page No. 52. Date of work June 25, 1986.

Replaced original stone with DNR aluminum monument with stamped cap.

See reverse side for corner diagram.

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date: November 18, 1986.

Signature

Certificate No.

[Seal]

AUDITOR'S CERTIFICATE

Filed for record this _____ day of ___ 19 In Book of Of Natural Resources. at page at the request

County Auditor

5.1.0 Survey of 1909 (Rhoder) BOSSCIESET BUYIN BROKE, STORE W/3 N=-CHC = ON W € E 5/5E5 SO DFIR NESSE 139L 40" DFIR COSE INTL 28' D Hem. 5360 56 38" D.FIR WIEW 30L 620 Survey of 1966 (Jelle) Set Pipe of E.L.M. ZMS CAP. 14" FIR NY84E SOL 9" Fin S36E 33.5L 7" HEM 533 1/20 46,5 L 10" FIR N3414W SSL Section Corner 7/3 TSAGN RSE Fours SK'SD. Piper w/ 2.LM. 20155 CAP & DRIG. STONE MARKED AS DESC. 30" F.A STUB (1909 87) WITH UIS. SCRIBE THE 4-1946 PEARING THEIS AS DESCRIBED Jelley Fd. THE S.E., S.W. F. N. W. 375 1N 1966

GORDON ERESSLER CORNER IS PIPE WIBIN BRASS CAF 3" ABOUE GROWD