

LAND CORNER RECORD

SKAMANIA

County

T. 7 N, R. 6 E, W.M.

Corner Code No. T-25

Segregated Surveys:

Name: ONE-QUARTER CORNER

Corner No.:

DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

Corner set by Lewis D. W. Shelton in 1900. Set a conglomerate stone 11"x9"x7", 8" in the ground. Marked Y4 on West Face from which:

A fir 8" diam. N87E 281ks. dist. marked Y4 S30 BT.

A fir 4" diam. N72W 161ks. dist. marked Y4 S25 B.T.

IN 1968 D.N.R. Remonumented corner with a 2" brass cap set in 3"x3" concrete monument.

2. Description of Evidence Found:

2" Brass cap set in 3"x3" concrete monument surrounded by rock collar.

A 26" fir snag with a burnt open blaze and visible
Scribing (S2) DNR Tag S72E 10.17 FT.

Cap marked

T7N R6E

EY4

25

1968

Washington Dept. of Natural Resources

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No.

BK 1, 853 Page No. 1, 2 Date of work 10/84

A 24" fir brs. S77E 29.01 FT. scribed Y4 S30 BT w/ brass washer
LS 18734 attached to face, also attached 54-3 / 54-4 signs / Painted
blaze / 6" band red.

Set a Reference Monument 30"x5/8" rebar w/ Alum. "SURV" CAP brs. S56W
8.08 ft. Cap reads

T7N R6E

S25 RM

1984

LS 18734

Set guard post w/ 54-3 / 54-4 attached.

Washington Plane Coordinates: Zone, Y, X

Order Accuracy. Derived From:

Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or
under my direction in compliance with the provisions of Chapter
50, Laws of 1973. Date 12/5/86

Signature

18734
Certificate No.



AUDITOR'S CERTIFICATE

Filed for record this day of 19 at M. In
Book of at page at the request of

County Auditor

Registered

Indexed, Sir

Filed

1

1111