

LAND CORNER RECORD

T 4N N, R 9E, W.M. County SKAMANIA
Segregated Surveys: Corner Code No. F-13
Name: Corner No.:
DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

CORNER ESTABLISHED BY DEPUTY SURVEYOR JACOB RICHARDSON UNDER CONTRACT No. 383, OCTOBER/NOVEMBER 1892, SET POST FROM WHICH BEARS:
4" WILLOW, N 40° E, 161Ks, Scribed "T4N R9E S3 BT"
24" FIR, S 30° E, 271Ks, " "T4N R9E S10 BT"
4" FIR, S 42° W, 371Ks, " "T4N R9E S9 BT"
6" FIR, N 70° W, 371Ks, " "T4N R9E S4 BT"
FILED FOR RECORD
SEAL - A G. WASH
BY TERRA SURVYORS


2. Description of Evidence Found:

24" D. FIR, NOW 53", S 30° E, 17.82 FT, WITH HEALED 13L 42E. D. W. Dp.
OCT 27 4 28 PM '87
OPENED AND FOUND SCRIBING AT PROPER AGE. AUDITOR
HARRY M. OLSON
NO TRACE OF SMALL FIRS OR WILLOW.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 4. Page No. 20. Date of work 5-7-87.

SET STANDARD 2 1/2" X 30" FOREST SERVICE ALUMINUM PIPE AND CAP 24" IN THE GROUND, FROM WHICH BEARS:
19" D. FIR, N 9°-45' E, 41.41 FT, Scribed "S3 BT"
53" D. FIR, S 30° E, 17.82 FT, WITH HEALED GLO BLAZE.
15" D. FIR, S 40°-30' W, 31.55 FT, Scribed "S9 BT"
14" D. FIR, N 57°-45' W, 28.12 FT, " "S4 BT"

TREES HAVE RED PAINTED BANDS, TAGS
AND BRASS WASHERS, "PLS 18731" SET CARSONITE
GUARD POST NEAR MONUMENT.



Washington Plane Coordinates: Zone, Y
Order Accuracy. Derived From:
Pin Pointed on Photo No. Date. Located at.

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date 10/10/87
Signature [Signature] Certificate No. 18731



AUDITOR'S CERTIFICATE

Filed for record this... day of ... 19... at ... M. In
Book ... of ... at page ... at the request of ...

County Auditor

Registered S

Index 201r
Indirect
Filed
Mailed