

LAND CORNER RECORD

T 4 N, R 9E, W.M. County SKAMANIA Corner Code No. E-16  
Segregated Surveys:  
Name: Corner No.:  
DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

NONE.

FILED FOR RECORD  
SKAMANIA CO. OASH  
BY TERRA SURVEYING

OCT 27 4 30 PM '87

AUDITOR  
GARY M. DISON

2. Description of Evidence Found:


NONE.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 10 Page No. 22 Date of work 7-87

SET RAILROAD SPIKE FOR CORNER IN SOUTHBOUND LANE OKLAHOMA RD. SET REFERENCE MONUMENT SOUTH ON PROPERTY LINE IN EAST TOE OF ROAD FILL. FROM SPIKE BEARS:

21" D. FIR, N34°30'E, 103.3 FT., SCRIBED "S3E 1/16 BT"  
17" D. FIR, S62°15'W, 30.8 FT., " "S10E 1/16 BT"  
2 1/2" x 30" ALUMINUM PIPE/CAP, S1°58'46"E, 85.00 FT.  
TREES HAVE RED PAINTED BANDS, 54-3 & 54-9 TAGS, AND BRASS "PLS 18731" WASHERS. SET CARBONITE GUARD POST WEST OF SPIKE.

R/R CHISELED SPIKE 'X'



Washington Plane Coordinates: Zone, Y, X

Order Accuracy. Derived From:

Pin Pointed on Photo No. Date. Located at.

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date 8/87

Signature

Certificate No. 18731



AUDITOR'S CERTIFICATE

Filed for record this day of 19 at M. In Book of at page at the request of

County Auditor

Form prescribed by Bureau of Surveys and Maps pursuant to the provisions of Section Chapter 50, Laws of 1973.

Registered

Indirect

Filmed

Mated