

LAND CORNER RECORD

T 5 N, R 9 E, W.M. County SKAMANIA
Segregated Surveys: Corner Code No. 2-13
Name: Corner No.:
DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.


1. History of Corner Establishment and Subsequent Restoration:
CORNER ESTABLISHED BY DEPUTY SURVEYOR JACOB RICHARDSON
UNDER HIS CONTRACT #383, DATED OCTOBER/NOVEMBER 1892. SET
POST FROM WHICH BEARS:
6" FIR, N 42-30'E, 37 IKs, MARKED "T 5N R 9E S 34 BT"
30" FIR, N 55°W, 33 IKs, " " "T 5N R 9E S 33 BT"
10" FIR, S 8°-30'W, 22 IKs, " " "T 5N R 9E SC S 33+34 BT"

2. Description of Evidence Found:
5" D. FIR, NOW 12" WINDFALL, N 42-30'E, 24.4' FEET
30" D. FIR, NOW 42", N 55°W, 21.78 FT. "BT" FOUND
10" D. FIR, NOW 16" SNAK, S 8°30'W, 14.52 FT.

FILED FOR RECORD
EXAMINED BY TERRA SURVEYING
OCT 28 9 29 AM '87
J. J. Webb, Dep.
AUDITOR
GARY M. OLSON

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 4 Page No. 20 Date of work 4-16-87

SET STANDARD FOREST SERVICE ALUMINUM MONUMENT (2 1/2" X 30"),
24" IN THE GROUND, WITH 25 STONES ALONG SIDE FROM WHICH BEARS:
34" D. FIR, N 83-45E, 80.81 FT. SCRIBED "S 34 BT"
32" D. FIR, S 89-30'W, 40.05 FT. SCRIBED "S 4 BT"
42" D. FIR, N 55°W, 21.78 FT WITH 640 BLAZE
TREES HAVE RED PAINTED BANDS, TAGS,
AND BRASS WASHERS "PLS 18731" SET CARBONITE
GUARD POST NEAR MONUMENT.



Washington Plane Coordinates: Zone, Y, X
Order Accuracy. Derived From:
Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or
under my direction in compliance with the provisions of Chapter
50, Laws of 1973. Date 10/28/87
Signature [Signature] Certificate No. 18731



AUDITOR'S CERTIFICATE

Filed for record this day of 19 at M. In
Book of at page at the request of

County Auditor

Registered S
Indexed, Jr
Amirco
Filmed
Mailed