

LAND CORNER RECORD

SKAMANIA County
T 5 N, R 9 E, W.M. Corner Code No. 2-21
Segregated Surveys: Corner No.:
Name: DLC, RES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.


- History of Corner Establishment and Subsequent Restoration:
CORNER ESTABLISHED BY DEPUTY SURVEYOR JACOB RICHARDSON UNDER
CONTRACT NO. 383, OCTOBER 1892, SET POST FROM WHICH BEARS:
9" MAPLE, N 35° 30' E, 43 Ks, SCRIBED T 5 N, R 9 E S 36 BT
20" FIR, N 23° 30' W, 23 Ks, SCRIBED T 5 N R 9 E S 35 BT
10" FIR, S 56° 30' W, 9 Ks, SCRIBED T 5 N R 9 E SC S 35 + 36 BT

- Description of Evidence Found:
20" D.F., Now 35" IN GOOD CONDITION WITH VISIBLE BLAZE
OTHER BT'S GONE.

FILED FOR RECORD
SKAMANIA CO. 1887
BY TERRA SURVEYING
OCT 28 9 51 AM '87
A. New, Dep.
AUDITOR
DARY OLSON

- Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 4 Page No. 14 Date of work 4-6-87

SET STD. FOREST SERVICE 2 1/2" x 30" ALUMINUM PIPE AND CAP,
24" IN THE GROUND FROM WHICH BEARS:
35" D.F. N 23° 30' W, 15.18 FT, WITH HEALED G.L.O. BLAZE
32" D.F. N 83° 30' E, 10.53 FT, SCRIBED "S 36 BT"
15" HEMLOCK S 8° 30' E, 54.10 FT, SCRIBED "T 4 N S 2 BT"
TREES HAVE RED PAINTED BANDS, TAGS
AND BRASS WASHERS "PLS 18731" SET CARSONITE
GUARD POST NEAR MONUMENT



Washington Plane Coordinates: Zone, Y, X
Order Accuracy. Derived From:
Pin Pointed on Photo No. Date. Located at.

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date 8/18/87

Signature

Certificate No. 18731

AUDITOR'S CERTIFICATE

Filed for record this day of 19 at M. In
Book of at page at the request of

County Auditor

Registered S
Indexed, Ir
Indexed
Filed
Mailed