

LAND CORNER RECORD

SKAMANIA County
T. 4 N, R. 9 E, W.M. Corner Code No. 9-17
Segregated Surveys: Corner No.:
Name: DLG, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

CORNER ESTABLISHED BY DEPUTY SURVEYOR JACOB RICHARDSON
UNDER HIS CONTRACT No. 383, OCTOBER/NOVEMBER 1892, SET POST
FROM WHICH BEARS:

15" FIR, N 70° W, 311 Ks., MARKED "1/4 SBT."
15" FIR, S 73° E, 76 Ks., " " "1/4 SBT"

FILED ON RECORD
OCT 28 10 39 AM '87
BY TERRA SURVEYING

2. Description of Evidence Found:


NO REMAINS OF GLO EVIDENCE FOUND

OCT 28 10 39 AM '87
J. J. Sub. Dep.
AUDITOR
CARY M. OLSON

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 4 Page No. 30 Date of work 7-87

SET STANDARD FOREST SERVICE 2 1/2" x 30"
ALUMINUM PIPE/CAP 24" IN THE GROUND, IN A
12" x 14" x 6" MOUND OF STONE, FROM WHICH BEARS:
23" W. FIR, S 80° 00' W, 22.8 FT, SCRIBED "S 10 1/4 BT."
18" D. FIR, S 5° 15' E, 4.3 FT, " " "S 11 1/4 BT."

TREES HAVE RED PAINTED BANDS, TAGS
AND BRASS "PLS 18731" WASHERS. SET CARSONITE
GUARD POST NEAR MONUMENT.




Washington Plane Coordinates: Zone, Y, X
Order Accuracy. Derived From:
Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or
under my direction in compliance with the provisions of Chapter
50, Laws of 1973. Date 9/87

Signature

Certificate No. 18731



AUDITOR'S CERTIFICATE

Filed for record this day of 19 at M. In
Book of at page at the request of

County Auditor

Form prescribed by Bureau of Surveys and Maps pursuant to the provisions of Section
Chapter 50, Laws of 1973.

Registered S
Indexed, air
Filed
Mailed