T. N. TRANTOW SURVEYING

412 W. Jefferson P.O. Box 287 Bingen, Washington 98605 (509) 493-3111

bingen, washington 20003 (302) 120 02
LAND CORNER RECORD
T. 3 N, R 9 E , W.M. SKAMANIA County Corner Code No. G-17
Name: \frac{1}{4} \text{ corner to Sections 10 & 11} Corner No.:
1. History of Corner Establishment and Subsequent Restoration: 2. Description of Evidence Found:
GLO set corner in 1880, from which bear: 4" maple, N20E, 9.90 feet 15" fir, S25W, 17.82 feet L.B. Smith (LS 5125) in 1956 did not recover corner, and used established fence corner for the position of this ½ corner. No remains of original BT's were found.
Accepted fencepos: for corner position, and set a 5/8x30" iron rod with plastic cap for this corner, at the NW corner of a south and east fenceline.
FILED FOR RECORD SKAMANIA CO. WASH BY ARAMMU SURVEYING
Jun 9 3 00 PM 198 AUDITOR GARY M. OLSON
3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. F.B. No30940 Page No. 14 Job No88388 Date of WorkMarch .30;1988 From the iron rod bear the following: 18" D-fir, N58E, 7.80 feet to nail @ center 18" D-fir, N52W, 9.14 feet to nail @ center 20" D-fir, S31W, 24.17 feet to nail @ center All trees marked with aluminum witness tags
Washington Plane Coordinates: South Zone, Y NA ,X third Order Accuracy. Derived From:
Pin Pointed on Photo No. NA Symbol Located at
SURVEYOR'S CERTIFICATE
This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Torigonal Date 12 May 1988 Certificate No. 15673
AUDITOR'S CERTIFICATE
Filed for record this day of 19 at RMC dod S Book of at page at the request of Internation
T. N. TRANTOW SURVEYING
Coi · · Auditor ħ