

105267

BOOK 319 PAGE 35

## T. N. TRANTOW SURVEYING

412 W. Jefferson P.O. Box 287

Bingen, Washington 98605 (509) 493-3111

## LAND CORNER RECORD

T. 3 N, R. 9 E, W.M. SKAMANIA County Corner Code No. 6-13

Name: 1 corner to Sections 9 &amp; 10 Corner No.:

DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

## 1. History of Corner Establishment and Subsequent Restoration: 2. Description of Evidence Found:

GLO established this corner in 1880, from which bear:

10" fir, S36E, 7.92 feet

14" fir, N26W, 14.52 feet

L.B. Smith (LS 5125) set corner by proportion with staff compass in 1956, and

set a 3/4"x30" iron pipe, from which bear:

5" fir, S76E, 10.0 feet, scribed 1/4SBT

8" fir, West, 10.00 feet, scribed 1/4SBT

Set new corner by proportion, and marked new trees.

FILED FOR RECORD  
SKAMANIA CO. WASH  
BY T. N. TRANTOW SURVEYINGJUN 9 3 16 PM '88  
AUDITOR  
GARY M. OLSON

## 3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record.

F.B. No. 30910-2 Page No. 10 Job No. 88393 Date of Work 19 May 1988

Set 5/8"x30" iron rod with plastic cap for the corner, from which bear:

12" D-fir, S34E, 5.25 feet to nail @ center, scribed WT

7" D-fir, S31W, 7.85 feet to nail @ center, scribed WT

6" D-fir, S82W, 10.77 feet to nail @ center, scribed WT

3/4" iron pipe, S38W, 17.24 feet

All trees marked with witness tags

Washington Plane Coordinates: South Zone, Y NA, X  
third Order Accuracy. Derived From:

Pin Pointed on Photo No. NA Symbol Located at


## SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973.

Signature

Date 22 May 1988

Certificate No. 15673



## AUDITOR'S CERTIFICATE

Filed for record this day of 19 at M. In  
Book of at page at the request of

T. N. TRANTOW SURVEYING

County Auditor

In:

Filed

Mailed