

LAND CORNER RECORD

SKAMANIA

County

T 5 N, R 9 E, W. 1.

Corner Code No. Z-25

Segregated Surveys:

Name:

Corner No.:

DLC, RES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite

1. History of Corner Establishment and Subsequent Restoration:

CORNER ESTABLISHED BY DEPUTY SURVEYOR JACOB RICHARDSON
 UNDER CONTRACT NO 383, OCTOBER, 1892. SET POST FROM
 WHICH BEARS:
 10" FIR, N58E, 23 LKS SCRIBED "TSN R10E S31BT"
 10" FIR, N9W, 58 LKS SCRIBED "TSN R9E S36BT"
 5" FIR, S64E, 4 LKS SCRIBED "SC TSN R9 & 10E BT"

2. Description of Evidence Found:


10" Doug FIR, Now 38" N58E, 54.78' with HEALED BLAZE
 10" Doug FIR, Now 36", N9W, 38.28' with HEALED BLAZE.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location Diagram corner and indicate meridian and reference to map of record, Surveyor's Field Book No.

4 Page No. 12 Date of work 3-31-87

SET STANDARD 2 1/2" X 30" ALUMINUM PIPE & CAP
 24" IN GROUND IN A 2' X 2' X 6" MOUND
 OF STONE, FROM WHICH BEARS:
 34" DOUG FIR N24-45W, 36.70', SCRIBED
 "S36 SCBT"
 29" DOUG FIR S72-45E, 67.50' SCRIBED
 "S1BT"

TREES HAVE RED PAINTED BAND, TAGS
 AND BRASS WASHER "PLS 18731" SET CASONITE
 POST NEAR MONUMENT



Washington Plane Coordinates: Zone, Y

Order Accuracy, Derived From:

Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or
 under my direction in compliance with the provisions of Chapter
 50, Laws of 1973. Date April 12, 1988

Signature

Certificate No. 18731



AUDITOR'S CERTIFICATE

Filed for record this day of 19 at M. In
 of at page at the request of

County Auditor

Form prescribed by Bureau of Surveys and Maps pursuant to the provisions of Section 5 (2),
 Chapter 50, Laws of 1973.

FILED FOR RECORD

SKAMANIA, WASH

BY TERRY

SURVEYING

APR 14 12 20 PM '88

AUDITOR

GARY H. GAYLORD