Mulled

## LAND CORNER RECORD

MAMPSTUR CORPORATION
1010 Douglas A3
LONGVIEW, WASHINGTON 98632

SKAMANIA \_N,R\_\_\_6 E.\_\_, W.M. County Segregated Surveys: Corner Code No.\_ Name: SW. Corner of Section 35 Corner No.: DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite. 1. History of Corner Establishment and Subsequent Restoration:
In 1900, Lewis Shelton originally established the corner with a post and scribed 4 BT's under GLO contract #552; then in 1921, Chester Pecore remonumented the corner with the iron pipe and brock accordance below and added 2 additional BT's to the South as he report iron pipe and brass cap shown below and added 2 additional BT's to the South as he reported the ones scribed in 1900 were down. Pecore's survey was under GLO contract, group #19. Then on July 19,1988, HAMPSTUR CORP. found the above mentioned brass cap monument along with 3 original BT's while performing a corner restoration project in the area for PLUM CREEK TIMBER CO. The corner was maintained and references added as shown below, under the 2. Description of Evidence Found: UniGINAL GLO CORNER: (2"x36" iron pipe, 28" deep with brass cap); found as described. -[1900 BT] (6" Hemlock, N450E--17 lks.); fd. 10" stump, 3 ft. high, with vis. axe work and face at record location.

-[1900 BT] (18" Fir, N59½0W--17 lks.); fd. decayed remains of uprooted stump.

-[1921 BT] (5" Cedar, S22ºE--12 lks.); fd. 30" stump with visible face at S20ºE--7 ft.

-[1921 BT] (18" Maple, S32º45'W--68 lks.); fd. 36" stump with visible axe work at record 3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. PS-056 Page No. 3-4 Date of work 7-18-1988 LOCATION; BD "X" FACING -on a 50% Northeast slope. -approx. 75 ft. West of a dry creek CREEK LOT, TH bed, which bears Northeast and 30 ft. East of a spring. -approx. 140 ft. South of "10 road" at a point which is 150 ft. Westerly of the center of a concrete bridge. FD. 640 2" IRON
PIPE WITH STAMPED
BEASS CAP, AS SET
IN 1921 BY C.W. PECURE. TOP CENTER OF FO. 30" CEPAR ETUMP (SEE FA) Washington Plane Coordinates: Zone. Order Accuracy. Derived From: Pin Pointed on Photo No. -Located at SURVEYOR'S CERTIFICATE This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date October 17, 1988 Signature Calvin J. Hampton #18,087 Certificate No SOJONAL LAND **AUDITOR'S CERTIFICATE** Filed fordecord fins day of\_\_ Book \_at. of\_ at page\_ \_at the request of SKAMAL BY Ragistered Indexed, 11 Form prescribed by Bureau of Surveys and Maps pursuant to the provisions of Section 5 (2), Indirect Chapter 50, Laws of 1973. Filmical

The state of the s