



107740

BOOK 6/6 PAGE 48

HAMPSTUR CORPORATION
1010 Douglas A3
LONGVIEW, WASHINGTON 98632

LAND CORNER RECORD

T. 6 N. R. 6 E. S. 6 W.M. SKAMANIA County
Segregated Surveys: 1/4 S.6/S.5 Corner Code No. C-5
Name: _____ Corner No.: _____
DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

This corner was originally established in 1921, by Chester Pecore under GLO contract, group #19, who set a 1"x36" iron pipe with a brass cap for the corner. The corner has been found and used at various times by various surveyors since that time. On July 28, 1988, R. Bogdon (from HAMPSTUR CORP.), located the corner and referenced the same as shown in the diagram below, while working on a "corner restoration" project for PLUM CREEK TIMBER COMPANY, under the direction of C. Hampton, LS #18,087.

2. Description of Evidence Found:

ORIGINAL GLO MONUMENT (1921): Found the 1"x36" iron pipe with brass cap as originally set in 1921, as mentioned above and shown in the diagram below.

ORIGINAL BT's (1921):

- 8" Hemlock, S56 $\frac{1}{2}$ °E--17 lks.; gone--position falls on edge of road.
- 8" Hemlock, N76 $\frac{1}{2}$ °W--13 lks.; fd an 18" stump, 2 ft. high at record location, see diagram below.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. PS-056 Page No. 23 Date of work 7-28-88

LOCATION:

- in a fenced test plot, 11.5 ft. West of fence.
- on an East slope, 17 ft. West of the centerline of road 1060, which bears N30°W & S10°E.
- approx. 100 ft. South of a draw which bears Southeast.
- approx. 100 ft. East from the top of a gentle hill.

1921 BT

FD. 18" HEMLOCK STUMP, 2 FT. HIGH. DROVE R-R SPIKE IN TOP CTR. "LOC-TAG"

NEW RP 28" FIR STUMP 18" TALL WITH R-R SPIKE IN TOP CTR. "LOC-TAG"

NEW RP 14" FIR STUMP 18" TALL WITH R-R SPIKE IN TOP CTR. "LOC-TAG"

SET 5 1/2 FT. STEEL FENCE POST WITH "LOC-TAG"

DEC. 19°E

FD. THE ORIG. GLO 1"x36" IRON PIPE WITH A STAMPED BRASS CAP, 0" HIGH

4"x4" REBAR POST IN FENCE LINE "LOC-TAG"

Washington Plane Coordinates: _____ Zone, Y
Order Accuracy. Derived From: _____
Pin Pointed on Photo No. _____ Date _____ Located at _____

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date August 28, 1989

Signature: Calvin S. Hampton, PLS LS #18,087
Certificate No.



AUDITOR'S CERTIFICATE

Filed for record this _____ day of _____ 19 _____ at _____ M. In _____ of _____ at page _____ at the request of _____

FILED FOR RECORD BY SKAMANIA COUNTY WA BY _____ AUG 30 1989 CARY H. OLSON COUNTY AUDITOR

Form prescribed by Bureau of Surveys and Maps pursuant to the provisions of Section 5 (2), Chapter 50, Laws of 1973.

Registered
Indexed, Dir
Indirect
Filed 9-1-89
Filed