107762



LAND CORNER RECORD

HAMPSTUR CORPORATION 1010 Douglas A3 LONGVIEW, WASHINGTON 98632

prox. 40 ft. West of a 25 ft. dia. boulder. the monument is situated on the South side of seminated in the series. an existing East-West cutting line: the mature timber to the North, approx. yr. old reprod to the SE. and approx. yr. old reprod to the SW. 1900 of the seminated in the SW. 1900 of the seminated in the semina	7 N.R 6 E. W.M. Bregated Surveys:	Corner Code No. Z-13
History of Cormer Establishment and Subsequent Restoration: This corner was originally established in 1900, by Lewis Shelton under GLO contract through 19, (an Iron pipe with brass cap was set that time, as shown below). The che corner was located by R. Bogdon (from HAPT CORP.) and re-referenced as indic many as located by R. Bogdon (from HAPT CORP.) and re-referenced as indic more than the diagram below, while working on a "corner restoration project for PLIM CREEK DEPANY, under the direction of C. Hampton, PLS #18,087. Description of Evidence Found: RIGINAL GLO MINIMENT: Found the 2"M26" iron pipe with stanced brass cap, as set in under a GLO contract, as mentioned above and shown in the diagram below. PRIGINAL BI's, (scribed in 1900 survey): -12" Cedar, NI76E25 lks.: fd. 23" Cedar stump at record location—see cliagram 20" Fir, Scribed-28 lks.; fd. a 36" Fir stump, 8 ft. high at record location—see "20" Fir, Scribed-28 lks.; fd. a 36" Fir stump, 8 ft. high, at rec. location—see "20" Fir, Scribed-28 lks.; fd. a 36" Fir stump, 8 ft. high, at rec. location—see "20" Fir, NI5°W23 lks.; fd. a 36" Fir stump, 8 ft. high, at rec. location—see "20" Fir, Scribed Department of the stump of record. Surveyor's Field Book No. 120 Fir. Scribed Department of the Scribed Departmen	me;sw corner of Section	on 34
Hillatory of Conner Establishment and Subsequent Restoration: This conner was originally established in 1900, by Lewis Shelton under GLO contract then Chester Percorr emonumented the corner in 1921, while working under GLO contract group #19, (an iron pipe with brass cap was set at that time, as shown below. On the care was been visited and used by various surveyors since that time. On August 30, 1988, in the diagram below, while working on a "corner restoration project for PLUM CREEK the corner was located by R. Bogdon (from HAMPSIUR CORP.) and re-referenced as indic morphally, under the direction of C. Hampton, PLS #18,087. Pescription of Evidence Found: RIGINN ALO MONNENT: Found the 2"x26" iron pipe with stanced brass cap, as set in "under a GLO contract, as mentioned above and shown in the diagram below. RIGINN BT's, (scribed in 1900 survey): -12" Cedar, M176F25 lks.; fd. 27" Cedar stump at record locationsee cliagram -26" fir, Scrybe27 lks.; fd. a 36" fir stump, and y 2 thing at record locationsee -22" fir, Scrybe28 lks.; fd. a 36" fir stump, and y 2 thing at record locationsee -22" fir, N176W23 lks.; fd. a 36" fir stump, a ft. high, at rec. locationsee -22" fir, N176W23 lks.; fd. a 36" fir stump, a ft. high, at rec. locationsee of the property of the student work and indicate meridian and reference to map of record. Surveyor's Field Book No. Incentional California of the North approx of the No	DLC, HES, Tract, Min	ning Claim, Indian Allotment, Federal Warner, Townsto
Then Chester Peopore remonumented the corner in 1920, by Lewis Shelton under GLO contract group #19 (an Iron pipe with brass cap was set at that time, as shown below.) on the carner was been visited and used by various surveyors since that time, as shown below. On the carner was been visited and used by various surveyors since that time, as shown below. On the carner was been visited and used by various surveyors since that time, as shown below. On the diagram below, while working on a "corner restoration project for PLUM CREEK in the diagram below, while working on a "corner restoration project for PLUM CREEK in the diagram below, while working on a "corner restoration project for PLUM CREEK RIGINAL BI's; for a mentioned above and shown in the diagram below. RIGINAL BI's; (scribed in 1900 survey): -12" Cedar, MI70E25 lks.; fd. 27" Cedar stump at record locationsee cliagram -20" Fir, S670e21 lks.; fd. a 36" Fir stump, and y 2 ft. high at record locationsee -22" Fir, S670e28 lks.; fd. a 36" Fir stump, and y 2 ft. high at record locationsee -22" Fir, S670e28 lks.; fd. a 36" Fir stump, and y 2 ft. high at record locationsee -22" Fir, N150w23 lks.; fd. a 36" Fir stump, and y 2 ft. high at record locationsee -22" Fir, N150w23 lks.; fd. a 36" Fir stump, and y 2 ft. high, at rec. locationsee of the second states and corollary Data to Perpetuate this Corner Location. Diagram of the second states and corollary Data to Perpetuate this Corner Location. Diagram of the second states and indicate meridian and reference to map of record. Surveyor's Field Book No. **DEAR** No. **D	listory of Corner Fatalitat	하는 것은 사람이 되는 것을 하는 것을 하는 것들이 있는 것이 하는 것이 하는 것이 없다. 그렇게 하는 것이 하는 것이 하는 것이다. 그렇게 하는 것이다. 그렇게 하는 것이다. 그렇게 하는 것이다. 그런 그렇게 되었다면 하는 것이다면 하
under a GLO contract, as mentioned above and shown in the diagram below. RIGINAL BI's; (scribed in 1900 survey): -12" Cedar, N179E-25 lks.; fd. 27" Cedar stump at record location-see Clagram -20" Fir, S619G-77 lks.; fd. a 36" Fir stump, all the record location-see Clagram -26" Fir, S479w-28 lks.; fd. a 36" Fir stump, B ft. high, at rec. location-see -22" Fir, N150w-23 lks.; fd. a 36" Fir stump, B ft. high, at rec. location-see -22" Fir, N150w-23 lks.; fd. a 36" Fir stump, B ft. high, at rec. location-see orders and corollary Data to Perpetuate this Corner Location. Diagram -22" Fir, N150w-23 lks.; fd. a 36" Fir stump, B ft. high, at rec. location-see orders and indicate meridian and reference to map of record. Surveyor's Field Book No. Acceptable of the See Northeast slope. Set Less of a creek, which brs. North. Of the East of a sharp ridge, lich bears to the Northese: lich bears t	hen Chester Pecore remonumented to roup #19, (an iron pipe with brass as been visited and used by various to the corner was located by R. Bogdown the diagram below, while working CMPANY, under the direction of C.	the corner in 1900, by Lewis Shelton under GLO contract # cs cap was set at that time, as shown below). The course surveyors since that time. On August 30, 1988,
certical H'S; (scribed in 1900 survey): -12" (cedar, NI70E-25 lks.: fd. 27" Cedar stump at record location—see Clagram -30" Fir, S6740E-77 lks.; fd. a 36" Fir stump, only 2 ft. high at record location—see -22" Fir, S470H-28 lks.; fd. a 36" Fir stump, 8 ft. high, at record location—see -22" Fir, NI50M-23 lks.; fd. a 36" Fir stump, 8 ft. high, at record location—see -22" Fir, NI50M-23 lks.; fd. a 36" Fir stump, 3 ft. high, at rec. location—see -22" Fir, NI50M-23 lks.; fd. a 36" Fir stump, 3 ft. high, at rec. location—see -22" Fir, NI50M-23 lks.; fd. a 36" Fir stump, 3 ft. high, at rec. location—see -22" Fir, NI50M-23 lks.; fd. a 36" Fir stump, 3 ft. high, at rec. location—see -22" Fir, NI50M-23 lks.; fd. a 36" Fir stump, 3 ft. high, at rec. location—see -22" Fir, NI50M-23 lks.; fd. a 36" Fir stump, 3 ft. high, at rec. location—see -22" Fir, NI50M-23 lks.; fd. a 36" Fir stump, 3 ft. high, at rec. location—see -22" Fir, NI50M-23 lks.; fd. a 36" Fir stump, 3 ft. high, at rec. location—see -22" Fir, NI50M-23 lks.; fd. a 36" Fir stump, 3 ft. high, at rec. location—see -22" Fir, NI50M-23 lks.; fd. a 36" Fir stump, 3 ft. high, at rec. location—see -22" Fir, NI50M-23 lks.; fd. a 36" Fir stump, 3 ft. high, at rec. location—see -22" Fir, NI50M-23 lks.; fd. a 36" Fir stump, 3 ft. high, at rec. location—see -22" Fir, NI50M-23 lks.; fd. a 36" Fir stump, 3 ft. high, at rec. location—see -22" Fir, NI50M-23 lks.; fd. a 36" Fir stump, 3 ft. high, at rec. location—see -22" Fir, NI50M-23 lks.; fd. a 36" Fir stump, 3 ft. high, at rec. location—see -22" Fir, NI50M-23 lks.; fd. a 36" Fir stump, 3 ft. high, at rec. location—see -22" Fir, NI50M-23 lks.; fd. a 36" Fir stump, 3 ft. high, at rec. location—see -22" Fir, NI50M-23 lks.; fd. a 36" Fir stump, 3 ft. high, at rec. location—see -22" Fir, NI50M-23 lks.; fd. a 36" Fir stump, 3 ft. high, at rec. location—see -22" Fir, NI50M-24 lks24" Fir,	CIGINAL GLO MUNIMENTA COMPANY	
CATION: In a steep Northeast slope. In a st	-12" Cedar, N179E25 lks.; f -30" Fir, S6710E77 lks.; fd	rvey): fd. 27" Cedar stump at record locationsee diagram
CATION: In a steep Northeast slope. In a st	escribe Monument A	
CATION: In a steep Northeast slope. If the west of a creek, which brs. North. If the stat of a sharp ridge, nich bears to the Northest. If the stat of a sharp ridge, nich bears to the Northest. If the stat of a sharp ridge, nich bears to the Northest. If the stat of a sharp ridge, nich bears to the Northest. If the stat of a sharp ridge, nich bears to the Northest. If the state of a sharp ridge, nich bears to the Northest. If the state of a sharp ridge, nich bears to the Northest. If the state of a sharp ridge, nich bears to the Northest side of state of	rener and indicate meridian and reference S-056 Page No. 45-46 Date of work	to map of record. Surveyor's Field Book No. 1900 87
in a steep Northeast slope. 5 ft. West of a creek, which brs. North. 6 ft. East of a sharp ridge, and the bears to the Northern prox. 40 ft. West of a 25 ft. dia. boulder. 7 in the bears to the Northern prox. 8 in the bears to the Northern prox. 9 in the mature timber to the North approx. 9 in the mature timber to the North approx. 9 in the mature timber to the SE. and approx. 9 in the don Photo No. 1		1900 BT RELL MA STRING S. CT. I
Surveyor's Certificate Surveyor's Certificate No Date Surveyor's Certificate No Date Surveyor's Certificate No Certificate No Date AUDITOR'S CERTIFICATE AUDITOR'S CERTIFICATE Of each of Auditor's Certificate No Date AUDITOR'S CERTIFICATE Auditor's Certificate No Date AUDITOR'S CERTIFICATE Auditor's Certificate No Date AUDITOR'S CERTIFICATE Auditor's Certificate No Date Auditor's Certificate No Date AUDITOR'S CERTIFICATE Auditor's Certificate No Date Auditor's Certificate No D		SET. NIENIELE 19 19 MARE IN CTR)
Surveyor's Certificate Surveyor's Certificate No Date Surveyor's Certificate No Date Surveyor's Certificate No Certificate No Date AUDITOR'S CERTIFICATE AUDITOR'S CERTIFICATE Of each of Auditor's Certificate No Date AUDITOR'S CERTIFICATE Auditor's Certificate No Date AUDITOR'S CERTIFICATE Auditor's Certificate No Date AUDITOR'S CERTIFICATE Auditor's Certificate No Date Auditor's Certificate No Date AUDITOR'S CERTIFICATE Auditor's Certificate No Date Auditor's Certificate No D	ft. West of a creek which	"LOC-TAG"
proprox. 40 ft. West of a 25 ft. dia. boulder. is monument is situated on the South side of 36" log lying E-W across the creek. an existing East-West cutting line: th mature timber to the North, approx. yr. old reprod to the SE, and approx. yr. old reprod to the SW. 1900	IV. Edst Of a chase "!"	
proc. 40 ft. west of a 25 ft. dia. boulder. the monument is situated on the South side of 36" log lying E-W across the creek. an existing East-West cutting line: th mature timber to the North, approx. yr. old reprod to the SE. and approx. yr. old reprod to the SW. Solve and approx. yr. old reprod to the SW. Solve and approx. yr. old reprod to the SW. Solve and approx. yr. old reprod to the SW. Solve and approx. Yr. old reprod to the SW. Solve and approx. Yr. old reprod to the SW. Solve and approx. Yr. old reprod to the SW. Solve and approx. Yr. old reprod to the SW. Solve and approx. Yr. old reprod to the SW. Solve and approx. Yr. old reprod to the SW. Solve and approx. Yr. old reprod to the SW. Solve and approx. Yr. old reprod to the SW. Solve and approx. Yr. old reprod to the SW. Yr. old	ich bears to the North	7 7 70, 3 3 3 6 10 6 10 6
an existing East-West cutting line: th mature timber to the North, approx. yr. old reprod to the SE, and approx. yr. old reprod to the SW. 1900 27 1914 For The Co. 1900 27 1914 For The Co. 1900 27 1914 For The Co. 1915 Fine Plane Coordinates: 2017 Fine Plane Coordinates: 2017 Fine Plane Coordinates: 2018 Fine Plane Coordinates: 2	Drox. 40 ft. West of a 25 ft die	THREE WAY DES. GLO BEAS
an existing East-West cutting line: th mature timber to the North, approx. yr. old reprod to the SE, and approx. yr. old reprod to the SE, and approx. yr. old reprod to the SW. 1900		
AUDITOR'S CERTIFICATE SURVEYOR'S CERTIFICATE SURVEYOR'S CERTIFICATE The state of	2 -/ - u GUITISS FDA OTONI	
syr. old reprod to the SE. and approx. yr. old reprod to	di existing soct Mask	AV
sign Plane Coordinates: Order Accuracy. Derived From: Inted on Photo No. Date Located at SURVEYOR'S CERTIFICATE Commer record correctly represents work performed by me or my direction in compliance with the provisions of Chapter was of 1973 Date LS \$18.087 Certificate No AUDITOR'S CERTIFICATE day of at page at the request of M. in		
Inted on Photo No. Date Located at SURVEYOR'S CERTIFICATE Corner record correctly represents work performed by me or my direction in compliance with the provisions of Chapter was of 1973 Date Located No. LS \$18.087 Certificate No AUDITOR'S CERTIFICATE day of		COX.
Inted on Photo No	To the Sw.	1900 07 6618
SURVEYOR'S CERTIFICATE corner record correctly represents work performed by me or my direction in compliance with the provisions of Chapter was of 1973. Date August 28, 1989 LS \$18.087 Certificate No AUDITOR'S CERTIFICATE Of		36 FM STURE SET SHET STEEL CTAG
Order Accuracy. Derived From: Inted on Photo No. DateLocated at SURVEYOR'S CERTIFICATE Corner record correctly represents work performed by me or my direction in compliance with the provisions of Chapter was of 1973 DateAugust 28, 1989 LS #18.087 Certificate NoAUDITOR'S CERTIFICATE Orecord IN		SPIKE IN TOP CIR) LOC. THE
SURVEYOR'S CERTIFICATE Corner record correctly represents work performed by me or my direction in compliance with the provisions of Chapter laws of 1973 Date	non Plane Coordinates:	
SURVEYOR'S CERTIFICATE corner record correctly represents work performed by me or my direction in compliance with the provisions of Chapter laws of 1973 Date	Order Accuracy. Derived From:	
SURVEYOR'S CERTIFICATE corner record correctly represents work performed by me or my direction in compliance with the provisions of Chapter laws of 1973 Date	ited on Photo No Date	
my direction in compliance with the provisions of Chapter ws of 1973-Date August 28, 1989 LS #18.D87 Certificate No AUDITOR'S CERTIFICATE day of		
my direction in compliance with the provisions of Chapter ws of 1973-Date August 28, 1989 LS #18.D87 Certificate No AUDITOR'S CERTIFICATE day of	SURVEYOR'S CERTIFICA	가 많이 하는 사람들이 보고 있는 사람들이 하는 것이 하는데 하는데 되었다. [178] 보고 있는 사람들이 되는 사람들이 보고 있는데 보고 있는데 보고 있다.
AUDITOR'S CERTIFICATE August 28, 1989 Augus	DIMPT PROOPS COMMONAL	
AUDITOR'S CERTIFICATE day of	my direction in compliance with the pr	rovisions of Charter
AUDITOR'S CERTIFICATE day of	We of 19/3 Date Rugust 28, 1989	2 raions of Chapter
AUDITOR'S CERTIFICATE day of		LS #18 097
ofat pageat the request ofM. In	Manual 1. Hampton, PLS	Certificate No
ofat pageat the request ofM. In	7 = 76	To POISTERLY AND
ofat pageat the request ofM. In	AllDitonic	OSPONIAL LING SUIT
ofat pageat the request ofM. In	Breco Links	CERTIFICATE
at pageat the request of	2 al	19
그리즘 공연 🚫 토 🧇 사용하는 이 회사가 되었다. 그는 사람들은 그 사용을 하는 그 그 사용을 받는다. 그는 그래 없는 것이 되었다.		at pageat the sequest of
	5.19	
rescribed by Bureau of Surveys and Maps pursuant to the provisions of Section 5 (2). Registered Indexed, Jir 7 100 Indexed, Jir 7		County Auditor Region