

## T. N. TRANTOW SURVEYING

412 W. Jefferson P.O. Box 287

Bingen, Washington 98605 (509) 493-3111

	LAND CORNER RECORD	
	T. 3 N, R 9 E , W.M. SKAMANIA County Corner Code No. J-19	
	Name: 4 section corner between Sec. 11 & 14 Corner No.:	
GLO establi 15" re	Corner Establishment and Subsequent Restoration: 2. Description of Evidence Fou shed this corner in 1879, from which bear: d cedar, N10E, 12 links (7.92 ft.) r, South, 16 links (10.56 ft.)	
at that tim	amania Co. employees accepted a 60-lb. rail section as the corner, and ne found a stump depression and wood fragments for the Sec. 11 5T. Rail ed in a 1980 survey by LS 15673, and others since then.	
2. The rail i	s at a slight angle, but firmly in the ground. The area has been logged.	
	St. AHAM D. WASH BY Transon Surveying	
	HAY 29 12 34 PM '90 Lowey	
	GARY M. OLSON Recisional American Ameri	
	Redirect Film, d. Lo 4400 Mensed	
gram corner	nument, Accessories and Corollary Data to Perpetuate this Corner Location. Dia- and indicate meridian and reference to map of record.  -1. Page No. 13 Job No. 89557 Date of Work Jan. 23, 1990	
14" D- 18" st	he RR iron bear the following: fir, N45W, 14.05 ft. to nail in face scribed \$11WT (rail measured at ground line; distance from top of rail is 13.73 ft.) ump, \$50E, 43.25 ft. to nail in face scribed \$14WT (rail at ground line; distance from top of rail is 43.88 ft.)	
Washington 1	Plane Coordinates: South Zone, Y, X	
***************	on Photo No. Symbol Located at.	
	SURVEYOR'S CERTIFICATE	
under my di	record correctly represents work performed by me or rection in compliance with the provisions of Chapter 1973 Landow Date 23 April 1990  Certificate No. 15673	
Filed for rego	AUDITOR'S CERTIFICATE  ord this 29th day of May 1990 at 12:34 PM. In of Monuments at page 41 at the request of Transous  ANTOW SURVEYING  Lary M. Olson by P. January - Disc	
T. N. TRA	ANTOW SURVEYING H MAIN AT THE request of Manager A	