

## LAND CORNER RECORD

Skamania

County

T 2 N, R. 6 E., W.M.Corner Code No. E-11

Segregated Surveys:

S. 1/4 Sec. 4

Name:

Corner No.:

DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

## 1. History of Corner Establishment and Subsequent Restoration:

G.L.O. survey in 1883 by Charles Sears

Set post 3' long 3" square, 24" in the ground for 1/4 corner

Silver Pine 40" diameter bears N. 65°30' W., 47 links dist.

Silver Pine 36" diameter bears S. 81° E., 50 links dist.

FILED FOR RECORD  
SKAMANIA WASH.BY Tennison Engineering

SEP 6 4 34 PM '91

P. Lowry

GARY M. OLSON

## 2. Description of Evidence Found:

Found mound of stones

Found 40" stump with tag marked S. 70° W., 35.0' (C.G.C. 10/30/51)

Registered /Indexed, Dir /Indirect /Filmed /Mailed /

## 3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. \_\_\_\_\_ Page No. \_\_\_\_\_ Date of work \_\_\_\_\_

Set 3/4" iron pipe with yellow plastic cap marked "PLS 11733" in mound of stones

Set B.T.'s as follows: 8" Fir, N. 45° W., 57.5 ft.

10" Douglas Fir, N. 58° W., 43.4 ft.


Set R.P.'s as follows: Set P.K. in center of 48" stump, N. 57° W., 49.5 ft.

Set P.K. in center of 40" stump (with existing tag) N. 71° E.  
37.15 ft.Washington Plane Coordinates: \_\_\_\_\_ Zone, Y, \_\_\_\_\_, X

Order Accuracy. Derived From: \_\_\_\_\_

Pin Pointed on Photo No. \_\_\_\_\_ Date \_\_\_\_\_ Located at \_\_\_\_\_

## SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date 8/26/91Signature David A. TuttleCertificate No. 11733

## AUDITOR'S CERTIFICATE

Filed for record this 16th day of September 1991 at \_\_\_\_\_ M. in Book 46 of Monuments at page 8 at the request of Tennison EngineeringGary M. Olson by P. Lowry - deputy  
County Auditor