

LAND CORNER RECORD

(THIS FORM PRESCRIBED BY THE PUBLIC LAND SURVEY OFFICE, DEPARTMENT OF NATURAL RESOURCES, PURSUANT TO RCW 58.09. ALPHA-NUMERIC INDEX DIAGRAM ON THE BACK.)

CORNER INDEXING INFORMATION:


TOW 2N RGE 6E CORNER CODE G-5
 (Willamette Meridian) (See instructions on back of LCR)

ADDITIONAL IDENTIFIER: (e.g., LCN designation for the corner, street intersection, plat name, block, lot, etc.)

116708

COUNTY: SKAMANIA

AUDITOR'S USE



BOOK 136 PAGE 612

AUDITOR

GARY M. OLSON

JUL 9 1 31 PM '93

P. Dowry

LAND SURVEYOR INFORMATION: (or Public Officer as per RCW 58.09.090)

This corner record correctly represents work performed by me or under my direction in conformance with the Survey Recording Act.

COMPANY OR AGENCY: TERRA SURVEYING

ADDRESS: P.O. BOX 617
HOOD RIVER, OR.
97031

June 3, 1993

Roy O. Gaylord

SEAL/SIGNATURE/DATE

WASHINGTON PLANE COORDINATES: N: E:

ORDER:

ZONE:

DATUM (Date of adjustment):

CORNER INFORMATION: Use the space below to provide the following information regarding the corner:

(1) Pertinent Corner History, (2) Evidence Found at the Corner, and (3) Corner Perpetuation Information. Please title and number the parts of your discussion accordingly. If additional space is needed use the back. (For (3), diagram the references. Also, provide the cross-refernce to a map of record, if applicable, the surveyor's field book no./page no., and the date of work.) (See the back of this form for the requirements of the Survey Recording Act.)

DNR HISTORY

1/2" REBAR WITH PLASTIC CAP

MARKED JIS #13518

DNR ALUMINUM CAP EXPOSED 3"

4 REFERENCE POINTS

.20" FIR AT N. 30° E. @ 22.26'

.16" HEMLOCK AT S. 95° E. @ 8.05'

.21" FIR AT S. 12° W. @ 20.71'

.24" FIR AT N. 84° W @ 15.69'

ALSO FOUND:

4" FIR BEARING TREE STUMP WITH
T/146 BARA OFF AND VISIBLE 0/10
AXE MARKS AT S. 71° E @ 9.90'

12" CEDAR BEARING TREE UPROOTED
AND FELL TO EAST, AT N 52° W @ 21.8'

TERRA

FOUND 3/4" DNE BRASS CAP EXPOSED 1"

AND IN GOOD CONDITION

CARSONITE POST BEARS SOUTH @ 0.6'

4" PPS

19" FIR STUMP BEARS S. 01° 11' 0 19.8'
STUMP IS 6.2' IN HEIGHT.

19" FIR STUMP BEARS N. 32° E @ 2.2'

STUMP IS 6.3' IN HEIGHT.

14" HEMLOCK STUMP BEARS S. 63° E @ 8.6'

21" FIR STUMP BEARS N. 87° W. @ 14.1'

STUMP IS 5.1' IN HEIGHT.

No additional references were set. Ask owner to root, "A" the bearing tree stumps.

Reference TERRA SURVEY #9135 of
MAY, 1993, FOR LONGVIEW FIBRE COMPANY,

DATE OF FORM: 2/92

9135

Registered	<input checked="" type="checkbox"/>
Indexed, Dir	<input checked="" type="checkbox"/>
Indirect	<input checked="" type="checkbox"/>
Filmed	<input checked="" type="checkbox"/>
Mailed	<input checked="" type="checkbox"/>

MARK THE CORNER LOCATION ON THE DIAGRAM BELOW AND FILL IN THE CORNER CODE BLANK ON THE OTHER SIDE:
(1) For corners located at the intersection of two lines (Section corners, quarter corners and sixteenth corners):

(a) The corner code is the alpha-numeric coordinate from the diagram below that corresponds to the appropriate intersection of lines.

(2) For corners that are not located at the intersection of two lines (Heander corners, DLC's, HES's, reservation boundaries, mining claims, etc.):

(a) For corners that are on one line only the corner code is the line designation and the related line segment; i.e., a corner on line S between "B" and "O" is designated BC-5.
(b) For corners that are between lines the corner code is both line segments; i.e., a corner in the SE1/4 of the SE1/4 of section 18 is designated MN-4-5.

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25

A																									
B																									
C	6		5		4		3		2		1														
D																									
E																									
F																									
G	7		6		5		4		3		2		1												
H																									
J																									
K																									
L		18		17		16		15		14		13													
M																									
N																									
O		19		20		21		22		23		24													
P																									
Q																									
R																									
S		30		29		28		27		26		25													
T																									
U																									
V																									
W																									
X		31		32		33		34		35		36													
Y																									
Z																									

RCW 58.09.060 (2) requires the following information on this form: an accurate description and location, in reference to the corner position, of all monuments and accessories (a) found at the corner and (b) placed or replaced at the corner; (c) basis of bearings used to describe or locate such monuments or accessories; and (d) corollary information that may be helpful to relocate or identify the corner position.

SPACE FOR ADDITIONAL COMMENT:

FIELD Book #1, PAGE 49

BOOK 136 PAGE 613

44011