

LAND CORNER RECORD

(THIS FORM PRESCRIBED BY THE PUBLIC LAND SURVEY OFFICE, DEPARTMENT OF NATURAL RESOURCES, PURSUANT TO RCW 58.09, ALPHA-NUMERIC INDEX DIAGRAM ON THE BACK.)

FILED FOR RECORD
SKAMANIA CO. WASH
BY *Roy Gaylord*

JUL 9 1 33 PM '93

P. Lowry
AUDITOR
GARY M. OLSON

CORNER INDEXING INFORMATION:

TWP 2N RGE 6E CORNER CODE E-7
(Willamette Meridian) (See instructions on back of LCR)

ADDITIONAL IDENTIFIER: (e.g., BLN designation for the corner, street intersection, plat name, block, lot, etc.)

BOOK 136 PAGE 614

116709


COUNTY: SKAMANIA AUDITOR'S USE

LAND SURVEYOR INFORMATION: (or Public Officer as per RCW 58.09.090)

This corner record correctly represents work performed by me or under my direction in conformance with the Survey Recording Act.

COMPANY OR AGENCY: TERRA SURVEYING

ADDRESS: P.O. Box 617
HOOD RIVER, OR.
97031



JUNE 3, 1993

Roy O. Gaylord

SEAL/SIGNATURE/DATE

WASHINGTON PLANE COORDINATES: N:

E:

ORDER:

ZONE:

DATUM (Date of adjustment):

CORNER INFORMATION: Use the space below to provide the following information regarding the corner: (1) Permanent Corner History, (2) Evidence Found at the Corner, and (3) Corner Perpetuation Information. Please title and number the parts of your discussion accordingly. If additional space is needed use the back. (For (3), diagram the references. Also, provide the cross-reference to a map of record, if applicable, the surveyor's field book no./page no., and the date of work.) (See the back of this form for the requirements of the Survey Recording Act.)

DNR HISTORY

CALCULATED NOT FOUND OR SET

TERRA

SET ALUMINUM MONUMENT SET IN Stone mound

SET STEEL FENCE POST Along Side

SET 5/8" X 30" IRON ROD WITH PLASTIC CAP

MARKED TERRA LS 18731

IRON ROD BEARS S. 21° W. @ 7.34'

SET 5/8" X 30" IRON ROD WITH PLASTIC CAP

MARKED TERRA LS 18731

IRON ROD BEARS S. 73° E @ 8.78'

Registered 6
Indexed, Dir 6
Indirect 6
Filmed 6
Mailed 6

True Compass Bearings were used to
LOCATE IRON ROD BEARINGS.

See Filed Survey PLAT Regarding The
ROCK BLUFF, The Found 60" Hemlock
STUMP, and why the GLO SURVEYOR
CHARLES E. SEARS Stubbed it in
in 1883.

REFERENCE TERRA SURVEY #9135 OF
MAY, 1993, FOR Longview Fibre, Company.

DATE OF FORM: 2/92

9135

MARK THE CORNER LOCATION ON THE DIAGRAM BELOW AND FILL IN THE CORNER CODE BLANK ON THE OTHER SIDE:

(1) For corners located at the intersection of two lines (Section corners, quarter corners and sixteenth corners):

(a) The corner code is the alpha-numeric coordinate from the diagram below that corresponds to the appropriate intersection of lines.

(2) For corners that are not located at the intersection of two lines (Meander corners, DLC's, MES's, reservation boundaries, mining claims, etc.):

(a) For corners that are on one line only the corner code is the line designation and the related line segment; i.e., a corner on line 5 between "B" and "C" is designated BC-5.

(b) For corners that are between lines the corner code is both line segments; i.e., a corner in the SE1/4 of the SE1/4 of section 18 is designated NN-4-5.

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
A																									
B																									
C																									
D																									
E																									
F																									
G																									
H																									
J																									
K																									
L																									
M																									
N																									
O																									
P																									
Q																									
R																									
S																									
T																									
U																									
V																									
W																									
X																									
Y																									
Z																									

BOOK 136 PAGE 615

RCW 58.09.060 (2) requires the following information on this form: an accurate description and location, in reference to the corner position, of all monuments and accessories (a) found at the corner and (b) placed or replaced at the corner; (c) basis of bearings used to describe or locate such monuments or accessories; and (d) corollary information that may be helpful to relocate or identify the corner position.

SPACE FOR ADDITIONAL COMMENT:

GLO Hemlock STUMP BEARS
N 49W AT 8 LINKS. The corner
was set from this stump using
the FACE of the STUMP. We
found an 'O' OVAL in the FACE
of the BURNED STUMP FACING THE
CORNER. THIS WAS PAINTED RED
AND A BEARING TREE TAG & WASHER
WERE ATTACHED.

FIELD BOOK #1, PAGES 42 & 43.

