

# LAND CORNER RECORD

(THIS FORM PRESCRIBED BY THE PUBLIC LAND SURVEY OFFICE, DEPARTMENT OF NATURAL RESOURCES, PURSUANT TO RCW 58.09, ALPHA-NUMERIC INDEX DIAGRAM ON THE BACK.)

FILED FOR RECORD  
SKAMANIA CO. WASH  
BY Terra Surveying

JAN 19 3 32 PM '94

*P. Olson*  
AUDITOR  
CARY M. OLSON

## CORNER INDEXING INFORMATION:

TWP 2N RGE 6E CORNER CODE E 11  
(Willamette Meridian) (See instructions on back of LCR)

ADDITIONAL IDENTIFIER: (e.g., BLM designation for the corner, street intersection, plat name, block, lot, etc.)

**118547**

BOOK 140 PAGE 941

1/4 CORNER 4  
9

COUNTY: SKAMANIA

AUDITOR'S USE

## LAND SURVEYOR INFORMATION: (or Public Officer as per RCW 58.09.090)

This corner record correctly represents work performed by me or under my direction in conformance with the Survey Recording Act.

COMPANY OR AGENCY: TERRA SURVEYING

ADDRESS: P.O. BOX 617  
HOOD RIVER, OR 97031



12/30/1993

*Roy O. Gaylord*

SEAL/SIGNATURE/DATE

WASHINGTON PLANE COORDINATES: N:

E:

ORDER:


ZONE:

DATUM (Date of adjustment):

**CORNER INFORMATION:** Use the space below to provide the following information regarding the corner:  
(1) Pertinent Corner History, (2) Evidence Found at the Corner, and (3) Corner Perpetuation Information. Please title and number the parts of your discussion accordingly. If additional space is needed use the back. (For (3), diagram the references. Also, provide the cross-reference to a map of record, if applicable, the surveyor's field book no./page no., and the date of work.) (See the back of this form for the requirements of the Survey Recording Act.)

ORIGINAL CORNER WAS SET BY CHARLES SEARS IN 1883.


Found LS #11733 IRON ROD with yellow CAP SET in MOUND OF STONE AS DESCRIBED BY THE LAND CORNER RECORD IN BOOK 26, PAGE 8 OF THE LAND CORNER RECORD BOOK. DATED 9/6/1991. ALL ACCESSORIES WERE IN GOOD SHAPE.



Registered ☒  
Indexed ☒  
Indirect ☒  
Filmed ☒  
Mailed ☒

MARK THE CORNER LOCATION ON THE DIAGRAM BELOW AND FILL IN THE CORNER CODE BLANK ON THE OTHER SIDE:

- (1) For corners located at the intersection of two lines (Section corners, quarter corners and sixteenth corners):
- (a) The corner code is the alpha-numeric coordinate from the diagram below that corresponds to the appropriate intersection of lines.
- (2) For corners that are not located at the intersection of two lines (Meander corners, DLC's, HES's, reservation boundaries, mining claims, etc.):
- (a) For corners that are on one line only the corner code is the line designation and the related line segment; i.e., a corner on line 5 between "B" and "C" is designated BC-5.
- (b) For corners that are between lines the corner code is both line segments; i.e., a corner in the SE1/4 of the SE1/4 of section 18 is designated MN-4-5.



BOOK 140, PAGE 942

RCW 58.09.060 (2) requires the following information on this form: an accurate description and location, in reference to the corner position, of all monuments and accessories (a) found at the corner and (b) placed or replaced at the corner; (c) basis of bearings used to describe or locate such monuments or accessories; and (d) corollary information that may be helpful to relocate or identify the corner position.

SPACE FOR ADDITIONAL COMMENT:

WE CONSTRUCTED A STONE MOUND 2' X 2' X 2' SOUTH @ 10<sup>1</sup> FEET FROM CORNER.

DNR SURVEY IN BOOK 3, PAGE 2 WAS USED AS A BEARING BASIS.

THE CORNER IS LOCATED IN A ROCK SLIDE AREA.

ALL ACCESSORIES ARE IN GOOD SHAPE.