

LAND CORNER RECORD

B:\3-8S17.M06

FILED FOR RECORD
SKAMANIA CO. WASH
BY *Dennis Peoples*

(THIS FORM PRESCRIBED BY THE PUBLIC LAND SURVEY OFFICE, DEPARTMENT OF NATURAL RESOURCES, PURSUANT TO RCW 58.09. ALPHA-ALPHABETIC INDEX DIAGRAM ON THE BACK.)

MAR 24 9 39 AM '94

CORNER INDEXING INFORMATION:

TWP 3N (Willamette Meridian) RGE 8E (See Instructions on back of LCR) CORNER CODE ML-6-7

D. Olsson
AUDITOR
GARY M. OLSON

ADDITIONAL IDENTIFIER: (e.g., BLM designation for the corner, street intersection, plot zone, block, lot, etc.)

BOOK 142 PAGE 70

118995

COUNTY: SKAMANIA COUNTY AUDITOR'S USE

LAND SURVEYOR INFORMATION: (or Public Officer as per RCW 58.09.090)

This corner record correctly represents work performed by me or under my direction in conformance with the Survey Recording Act.

COMPANY OR AGENCY: D2AB Surveying Inc.

ADDRESS: 22 Cottontail Ridge Road,
White Salmon, Wa. 98672
Phone Number 1-509-493-3376



SEAL/SIGNATURE/DATE

WASHINGTON PLANE COORDINATES: N: _____ E: _____

ORDER: _____ ZONE: _____ DATUM (Date of adjustment): _____

CORNER INFORMATION: Use the space below to provide the following information regarding the corner: (1) Pertinent Corner History, (2) Evidence Found at the Corner, and (3) Corner Presentation Information. Please title and number the parts of your discussion accordingly. If additional space is needed use the back. (For (3), diagram the references. Also, provide the cross-reference to a map of record, if applicable, the surveyor's field book no./page no., and the date of work.) (See the back of this form for the requirements of the Survey Recording Act.)

SET 5/8" IRON ROD WITH 2.5" AL. CAP. SOUTH 1.2' OF WEST/EAST FENCE LINE
FOUND 3/4 IRON PIPE NORTH 1.40' IN FENCE LINE
FOUND 5/8" IRON ROD N85° 46' 18"W, 30.47'
3/4" IRON PIPE N86° 07' 41"W, 29.91'
3/4" IRON PIPE N86° 34' 32"W 30.71'
CALC. 1/64 CORNER N88° 16' 17"W 28.22'
THIS SURVEY SET WAS BASED OFF OLSON CONTROL AND D2AB TIES FOR A ROGERS SHORT PLAT.
THE SET IS ON THE 1/64 LINE AT THE OLD 1906 SENIOR DEED CALL OF 80 RODS RECORDED IN
BOOK 119 PAGE 940. IT FITS OLD FENCE REMAINS RUNNING TO THE NORTH.

Registered _____
Indexed, Dir _____
Indirect _____
Filmed _____
Revised _____

MARK THE CORNER LOCATION ON THE DIAGRAM BELOW AND FILL IN THE CORNER CODE BLANK ON THE OTHER SIDE.

- (1) For corners located at the intersection of two lines (Section corners, quarter corners and sixteenth corners):
 - (a) The corner code is the alpha-numeric coordinate from the diagram below that corresponds to the appropriate intersection of lines.
- (2) For corners that are not located at the intersection of two lines (Meander corners, D.L.C.'s, H.E.S.'s, reservation boundaries, mining claims, etc.):
 - (a) For corners that are on one line only the corner code is the line designation and the related line segment; i.e., a corner on line B between "D" and "E" is designated BC-D.
 - (b) For corners that are between lines the corner code is both line segments; i.e., a corner in the SE1/4 of the SE1/4 of section 1B is designated MB-4-S.

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25

A																												
B																												
C		6			5			4			3			2			1											
D																												
E																												
F																												
G		7			8			9			10			11			12											
H																												
J																												
K																												
L		18			17			16			15			14			13											
M																												
N																												
O																												
P		19			20			21			22			23			24											
Q																												
R																												
S																												
T		30			29			28			27			26			25											
U																												
V																												
W																												
X		31			32			33			34			35			36											
Y																												

RCW 58.09.060 (2) requires the following information on this form: an accurate description and location, in reference to the corner position, of all monuments and accessories (a) found at the corner and (b) placed or replaced at the corner; (c) basis of bearings used to describe or locate such monuments or accessories; and (d) ancillary information that may be helpful to relocate or identify the corner position.

SPACE FOR ADDITIONAL COMMENT:

UNOFFICIAL COPY