

LAND CORNER RECORD

3-8S17.L06

FILED FOR RECORD
SKAMAMIA CO. WASH
BY *Dennis Peoples*

(THIS FORM PRESCRIBED BY THE PUBLIC LAND SURVEY OFFICE, DEPARTMENT OF NATURAL RESOURCES, PURSUANT TO RCW 58.08, ALPHABETIC INDEX DIAGRAM (IN THE BACK).)

CORNER INDEXING INFORMATION:

TWP 3N RGE 8E CORNER CODE L-6-7
(Willamette Meridian) (See instructions on back of LCR)

ADDITIONAL IDENTIFIER: (a.g., BLM designation for the corner, street intersection, plat name, block, lot, etc.)

118996

BOOK 142 PAGE 72

COUNTY: SKAMAMIA COUNTY


AUDITOR'S USE

LAND SURVEYOR INFORMATION: (or Public Officer as per RCW 58.08.090)

This corner record correctly represents work performed by me or under my direction in conformance with the Survey Recording Act.

COMPANY OR AGENCY: D2AB Surveying Inc.

ADDRESS: 22 Cottontail Ridge Road,
White Salmon, Wa. 98672
Phone Number 1-509-493-3376



SEAL/SIGNATURE/DATE

WASHINGTON PLANE COORDINATES: N: E:

ORDER: ZONE: DATUM (date of adjustment):

CORNER INFORMATION:

Use the space below to provide the following information regarding the corner:
(1) Pertinent Corner History, (2) Evidence Found at the Corner, and (3) Corner Fabrication Information. Please title and number the parts of your discussion accordingly. If additional space is needed use the back. (For (3), diagram the references. Also, provide the cross-reference to a map of record, if applicable, the surveyor's field book no./page no., and the date of work.) (See the back of this form for the requirements of the Survey Recording Act.)

SET 5/8" IRON ROD WITH 2.5" AL CAP. AT THE WEST SHOULDER OF THE ROAD
FROM OLSON CONTROL MONUMENTS
FOUND 3/4" IRON PIPE MAY HAVE BEEN BENT, N88° 30' 49"W, 29.31' OLSON C-W1/16 S17
5/8" IRON ROD 1738-D OLSON CONTROL MON. S52° 05' 25"W, 26.32'
1/2" IRON ROD AT SOUTH FENCE CORNER S 1° 20' 28"W, 45.53'
THIS IS ON THE 1/16 LINE AT THE OLD [1906] DEED CALL, DISTANCE OF 80 RODS [RECORDED
IN BOOK 119 PAGE 940]. THIS DEED IS A SENIOR. THIS FITS OLD FENCE REMAINS RUNNING
SOUTH FROM THIS CORNER.

Registered ☒
Indexed, Dir ☒
Indirect ☒
Filmed ☒
Mailed ☒

MARK THE CORNER LOCATION ON THE DIAGRAM BELOW AND FILL IN THE CORNER CODE BLANK ON THE OTHER SIDE:

- (1) For corners located at the intersection of two lines (Section corners, quarter corners and sixteenth corners):
 - (a) The corner code is the alpha-numeric coordinate from the diagram below that corresponds to the appropriate intersection of lines.
- (2) For corners that are not located at the intersection of two lines (Meander corners, D.C.'s, H.E.'s, reservation boundaries, mining claims, etc.):
 - (a) For corners that are on the line only the corner code is the line designation and the related line segment; i.e., a corner on line 5 between "B" and "C" is designated BC-5.
 - (b) For corners that are between lines the corner code is both line segments; i.e., a corner in the SE1/4 of the SE1/4 of section 10 is designated NE-4-W.

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
A																									
B																									
C			6				5				4				3			2					1		
D																									
E																									
F																									
G			7				8				9				10			11					12		
H																									
I																									
J																									
K																									
L			18				17				16				15			14					13		
M																									
N																									
O																									
P			19				20				21				22			23					24		
Q																									
R																									
S																									
T			30				29				28				27			26					25		
U																									
V																									
W																									
X			31				32				33				34			35					36		
Y																									

RCM 58.69.060 (2) requires the following information on this form: (a) an accurate description and location, in reference to the corner position, of all monuments and accessories (a) found at the corner and (b) placed or replaced at the corner; (c) basis of bearings used to describe or locate such monuments or accessories; and (d) corollary information that may be helpful to relocate or identify the corner position.

SPACE FOR ADDITIONAL COMMENT: