

125036  
**LAND CORNER RECORD**

(THIS FORM PRESCRIBED BY THE PUBLIC LAND SURVEY OFFICE, DEPARTMENT OF NATURAL RESOURCES, PURSUANT TO RCW 58.09. ALPHA-NUMERIC INDEX DIAGRAM ON THE BACK)

BOOK 156 PAGE 601

FILED FOR RECORD  
SKAMANIA CO. WASH  
BY Olson Engineering

**CORNER INDEXING INFORMATION:**

TWP 3 North RGE 8 East CORNER CODE T-17  
(Willamette Meridian) (See instructions on back of LCR)

APR 17 8 46 AM '96

ADDITIONAL IDENTIFIER: (e.g. BLM designation for the corner, street intersection, plat name, block, lot, etc.)


*Olson*  
AUDITOR  
GARY M. OLSON

EAST QUARTER 27 COUNTY: SKAMANIA  
LAND SURVEYOR INFORMATION: (or Public Officer as per RCW 58.09.090)

AUDITOR'S USE

This corner record correctly represents work performed by me or under my direction in conformance with the Survey Recording Act.


COMPANY OR AGENCY: **OLSON ENGINEERING, INC.**  
1111 BROADWAY  
ADDRESS: **VANCOUVER, WA 98660**



WASHINGTON PLANE COORDINATES: N: E:

ORDER: ZONE: DATUM (Date of adjustment):

**CORNER INFORMATION:** Use the space below to provide the following information regarding the corner:  
(1) Pertinent Corner History, (2) Evidence Found at the Corner, and (3) Corner perpetuation information. Please title and number the parties of your discussion accordingly. If additional space is needed use the back. (For (3), diagram the references. Also, provide the cross-reference to a map of record, if applicable, the surveyor's field book no./page no., and the date of work). (See the back of this form for the requirements of the Survey Recording Act).



The original quarter corner was established by Deputy Surveyor Spray in 1875 as a post with accessories of a 12" Maple, South 55° East, 22 links and a 14" Maple, North 30° West 35 links.

In 1935 the U.S. Engineering Department set a monument with a brass cap in this position 2543.0 feet North of the Southeast corner of Section 27 (Bonneville Project-Lands # R 0-17-6 W.S.)

In 1938 the Bonneville Power Administration found the brass cap still existed (transit Book 15 page 72-74).

In 1991 Olson Engineering calculated this position based on the U.S. Engineering Department Map.

**OLSON**  
ENGINEERING INC.

LAND SURVEYORS  
ENGINEERS

1111 BROADWAY, VANCOUVER, WA 98660  
360-695-1385

Registered  
Indexed, Dir ☒  
Indirect ☒  
Filmed  
Mailed

MARK THE CORNER LOCATION ON THE DIAGRAM BELOW AND FILL IN THE CORNER CODE BLANK ON THE OTHER SIDE

(1) For corners located at the intersection of two lines (Section corners, quarter corners and sixteenth corners):

(a) The corner code is the alpha-numeric coordinate from the diagram below that corresponds to the appropriate intersection of lines.

(2) For corners that are not located at the intersection of two lines (Meander corners, DLC's, HES's, reservation boundaries, mining claims, etc.):

(a) For corners that are on one line only the corner code is the line designation and the related line segment; i.e., a corner on line 5 between "B" and "C" is designated BC-5.

(b) For corners that are between lines the corner code is both line segments; i.e., a corner in the SE1/4 of the SE1/4 of section 18 is designated NK-4-5.

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25

A																										
B																										
C		6				5					4				3				2				1			
D																										
E																										
F																										
G		7				8					9				10				11				12			
H																										
J																										
K																										
L		18				17					16				15				14				13			
M																										
N																										
O																										
P		19				20					21				22				23				24			
Q																										
R																										
S																										
T		30				29					28				27				26				25			
U																										
V																										
W																										
X		31				32					33				34				35				36			
Y																										
Z																										

RCM 58.09.060 (2) requires the following information on this form: an accurate description and location, in reference to the corner position, of all monuments and accessories (a) found at the corner and (b) placed or replaced at the corner; (c) basis of bearings used to describe or locate such monuments or accessories; and (d) corollary information that may be helpful to relocate or identify the corner position.

SPACE FOR ADDITIONAL COMMENT: