

125037
LAND CORNER RECORD

(THIS FORM PRESCRIBED BY THE PUBLIC LAND SURVEY OFFICE, DEPARTMENT OF NATURAL RESOURCES, PURSUANT TO RCW 58.09. ALPHA-NUMERIC INDEX DIAGRAM ON THE BACK.)

CORNER INDEXING INFORMATION:

TWP 3 North RGE 8 East CORNER CODE V-15
 (Willamette Meridian) (See Instructions on back of LCR)

ADDITIONAL IDENTIFIER: (e.g. BLM designation for the corner, street intersection, plat name, block, lot, etc.)

BOOK 156 PAGE 603

FILED FOR RECORD
 SKAMANIA CO. WASH
 BY Olson Engineering

APR 17 8 48 AM '96

P. Sawyer

AUDITOR

GARY M. OLSON

North Quarter 34 COUNTY: SKAMANIA

LAND SURVEYOR INFORMATION: (or Public Officer as per RCW 58.09.090)


AUDITOR'S USE

This corner record correctly represents work performed by me or under my direction in conformance with the Survey Recording Act.

COMPANY OR AGENCY: OLSON ENGINEERING, INC.

1111 BROADWAY

VANCOUVER, WA 98660



WASHINGTON PLANE COORDINATES: N:


ORDER:

ZONE:

DATUM (Date of adjustment):

CORNER INFORMATION: Use the space below to provide the following information regarding the corner:

(1) Pertinent Corner History, (2) Evidence Found at the Corner, and (3) Corner perpetuation Information. Please title and number the parts of your discussion accordingly. If additional space is needed use the back. (For (3), diagram the references. Also, provide the cross-reference to a map of record, if applicable, the surveyor's field book no./page no., and the date of work). (See the back of this form for the requirements of the Survey Recording Act).



The original quarter corner was a post established by Deputy Surveyor Spray in 1875 with the accessories of a 5" Ash, North 75° East, 30 links and a 4" Ash, South 35° East, 10 links.

In 1935 the U.S. Engineering department found an iron pipe in the North quarter corner position and measured to the Northwest and Northeast section corners distances of 2625.86 feet and 2696.80 feet respectively. (Bonneville Project - Lands, Ref. # 0-17-6 W.S.)

In 1991 Olson Engineering did not find the iron pipe and calculated the position based on the U.S. Engineering Department Survey.

Registered
 Indexed, Dir
 Indirect
 Filmed
 Mailed

OLSON
 ENGINEERING INC.

LAND SURVEYORS
 ENGINEERS
 1111 BROADWAY, VANCOUVER, WA 98660
 360-888-1344

BOOK 156 PAGE 604

MARK THE CORNER LOCATION ON THE DIAGRAM BELOW AND FILL IN THE CORNER CODE BLANK ON THE OTHER SIDE:

(1) For corners located at the intersection of two lines (Section corners, quarter corners and sixteenth corners):
(a) The corner code is the alpha-numeric coordinate from the diagram below that corresponds to the appropriate intersection of lines.
(2) For corners that are not located at the intersection of two lines (Meander corners, DLC's, HES's, reservation boundaries, mining claims, etc.):
(a) For corners that are on one line only the corner code is the line designation and the related line segment; i.e., a corner on Line 5 between "B" and "C" is designated PC-5.
(b) For corners that are between lines the corner code is both line segments; i.e., a corner in the SE1/4 of the SE1/4 of section 18 is designated MN-4-5.

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25

A																								
B																								
C	6		5		4		3		2		1													
D																								
E																								
F																								
G	7		8		9		10		11		12													
H																								
I																								
K																								
L	10		11		12		13		14		15													
M																								
N																								
U																								
P																								
Q																								
R																								
S																								
T																								
U																								
V																								
W																								
X	31		32		33		34		35		36													
Y																								
Z																								

RCH 58.09.060 (2) requires the following information on this form: an accurate description and location, in reference to the corner position, of all monuments and accessories (a) found at the corner and (b) placed or replaced at the corner; (c) basis of bearings used to describe or locate such monuments or accessories; and (d) corollary information that may be helpful to relocate or identify the corner position.

SPACE FOR ADDITIONAL COMMENT: