

125038
LAND CORNER RECORD

(THIS FORM PRESCRIBED BY THE PUBLIC LAND SURVEY OFFICE, DEPARTMENT OF NATURAL RESOURCES, PURSUANT TO RCW 58.09. ALPHA-NUMERIC INDEX DIAGRAM ON THE BACK.)

CORNER INDEXING INFORMATION:

TWP 3 North RGE 8 East CORNER CODE 3, T-15, 16
(Willamette Meridian) (See Instructions on back of LCR)

ADDITIONAL IDENTIFIER: (e.g. BLM designation for the corner, street intersection, plot name, block, lot, etc.)

BOOK 156 PAGE 605
FILED FOR RECORD
SKAMANIA CO. WASH
BY Olson Engineering

APR 17 8 50 AM '96


G. M. Olson
AUDITOR
GARY M. OLSON

NE CORNER WILLIAM MURPHY COUNTY: SKAMANIA
LAND SURVEYOR INFORMATION: (or Public Officer as per RCW 58.09.090)

AUDITOR'S USE

This corner record correctly represents work performed by me or under my direction in conformance with the Survey Recording Act.


COMPANY OR AGENCY: OLSON ENGINEERING, INC.
1111 BROADWAY
ADDRESS: VANCOUVER, WA 98660



WASHINGTON PLANE COORDINATES: N: E:

ORDER: ZONE: DATUM (Date of adjustment):

CORNER INFORMATION: Use the space below to provide the following information regarding the corner:
(1) Partient Corner History, (2) Evidence Found at the Corner, and (3) Corner perpetuation Information. Please title and number the parties of your discussion accordingly. If additional space is needed use the back. (For (3), diagram the references. Also, provide the cross-reference to a map of record, if applicable, the surveyor's field book no./page no., and the date of work). (See the back of this form for the requirements of the Survey Recording Act).



The original Northeast corner was a post established by E.P. McCormack in 1878 with the accessories of a 12" Fir, South 40° West, 80 links and a 36" Fir, North 25° East, 109 links.

In 1935 the U.S. Engineering Department surveying for the Bonneville Project found a stake with bearing trees and set a monument. (Bonneville Project - Lands Ref # R 0-17-6 W.S.)

Olson Engineering found a brass cap in this position 2724.02 feet North of the South line of Section 27, Township 3 North, Range 8 East.

OLSON
ENGINEERING INC.

LAND SURVEYORS
ENGINEERS
1111 BROADWAY, VANCOUVER, WA 98660
360-885-1385

Registered ☒
Indexed, Dir ☒
Indirect ☒
Plotted ☐
Titled ☐

MARK THE CORNER LOCATION ON THE DIAGRAM BELOW AND FILL IN THE CORNER CODE BLANK ON THE OTHER SIDE.

(1) For corners located at the intersection of two lines (Section corners, quarter corners and sixteenth corners):

(a) The corner code is the alpha-numeric coordinate from the diagram below that corresponds to the appropriate intersection of lines.

(2) For corners that are not located at the intersection of two lines (Meander corners, DLC's, HES's, reservation boundaries, mining claims, etc.):

(a) For corners that are on one line only the corner code is the line designation and the related line segment; i.e., a corner on line 5 between "B" and "C" is designated BC-5.

(b) For corners that are between lines the corner code is both line segments; i.e., a corner in the SE1/4 of the SE1/4 of section 18 is designated MN-4-5.

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
A																									
B																									
C		6			5				4					3				2						1	
D																									
E																									
F																									
G		7			8				9					10				11						12	
H																									
J																									
K																									
L		18			17				16					15				14						13	
M																									
N																									
O																									
P		19			20				21					22				23						24	
Q																									
R																									
S																									
T		30			29				28					27				26						25	
U																									
V																									
W																									
X		31			32				33					34				35						36	
Y																									
Z																									

RCM 58.09.060 (2) requires the following information on this form: an accurate description and location, in reference to the corner position, of all monuments and accessories (a) found at the corner and (b) placed or replaced at the corner; (c) basis of bearings used to describe or locate such monuments or accessories; and (d) corollary information that may be helpful to relocate or identify the corner position.

SPACE FOR ADDITIONAL COMMENT: