DEED RECORD 27

SKAMANIA COUNTY, WASHINGTON

Greenleaf Slough, said point lying S. 45° 27' 27" E., a distance of 688.83 feet from an iron pipe marking the witness corner which is 114.72 feet north of the section corner common to Section 16, 17, 20 and 21, T. 2 N., R., 7 E. W.M.; thence N. 32° 27' 30" E. a distance of 4822.54 feet to Survey Station 103 + 90.00; thence N. 39° 45' 30" E. a distance of 3439.38 feet to Survey Station 122 + 79.38, a point on the section line common to Sections 9 and 16, said point lying S. 89° 48' 55" W: a distance of 1371.92 feet from an iron pipe marking the section corner common to Sections 9 and 10, T. 2 N. R. 7 E. W.M., thence continuing N. 39° 45' 30" E. a distance of 3527.50 feet to Survey Station 158 + 06.88, a point on the East-West center line of Section 10, said point lying S. 89° 43° 38" E. 886.92 feet from a stake in a mound of rock marking the section corner common to Sections 9 and 10, T. 2 N., R. 7 E. W. M.; thence continuing N. 39° 45' 30" E. a distance of 393.12 feet to Survey Station 162 + 00; thence N. 39° 02' 40" E. a distance of 1133.48 feet to Survey Station 173 + 33.48 back = 173 + 35.00 ahead; thence N. 26° 46' 30" E. a distance of 1556.08 feet to Survey Station 188 + 91.08, a point on the section line common to Sections 3 and 10, said point lying N. 89° 57' 06" W. 257.86 feet from an iron pipe marking the $\frac{1}{4}$ section corner common to Sections 3 and 10, T. 2 N., R. 7 E., W. M.; thence continuing N. 26° 46' 30" E. a distance of 167.05 feet to Survey Station 190 + 58.13; thence N. 46° 50' 45" E. a distance of 2891.87 feet to Survey Station 219:+ 50; thence N. 43° 55' 21" E. a distance of 289.35 feet to Survey Station 219.+ 30; thence N. 43° 33' 21" E. a distance of 207.33 feet to Survey Station 222 + 39.35, a point on the section line common to Sections 2 and 3, said point lying S. 0° 33' 17" W. 167.99 feet from an iron pipe marking the west ½ section corner of Section 2, T. 2 N., R. 7 E., W.M.; thence continuing N. 43° 55' 21" E. a distance of 259.62 feet to Survey Station 224 + 98.97 back = 225 + 00.00 ahead; thence N. 39° 41' 30" E. a distance of 3395.43 feet to Survey Station 258 + 95.43, a point on the section line common to section 2, T. 2 N., R. 7 E. and Section 35, T. 3 N., R. 7 E., W.M., said point lying N. 89° 24' 31" W. 232.24 feet from an iron pipe in a mound of rock marking the 4 section corner common to Section 2, T. 2 N., R. 7 E. and Section 35, T. 3 N., R. 7 E., W.M.; thence continuing N. 39° 41' 30" E. a distance of 1260.57 feet to Survey Station 271 + 56.00; thence N. 39° 44' 50" E. a distance of 1044.00 feet to Survey Station 282 + 00; thence N. 41° 01' 15" E. a distance of 1845.74 feet to Survey Station 300 + 45.74, a point on the section line common to Sections 35 and 36, said point lying N. 0° 16' 20" E. 526.28 feet from an iron pipe and brass plate marking the $\frac{1}{4}$ section-corner common to Sections 35 and 36, T. 3 N., R. 7 E., W.M.; thence continuing N. 41° 01' 15" E. a distance of 2544.26 feet to Survey Station 325 + 90.00; thence N. 76° 41' 45" E. a distance of 734.71 feet to Survey Station 333 + 24.71, a point on the section line common to Sections 25 and 36, said point lying N. 89° 18' 24" W. 271.96 feet from a cross on a rock marking the 4 section corner common to Sections 25 and 36, T. 3 N., R. 7 E., WM.; thence continuing N. 76° 41' 45" E. a distance of 3019.77 feet to Survey Station 363 + 44.48, a point on the range line between Ranges 7 and 7½ E., said point lying N. 1°11' 17" E. 665.10 feet from a U.S.E.D. monument marking the section corner common to Sections 25 and 36, T. 3 N., R. 7 E., W.M.; thence continuing N. 76° 41' 45" E. a distance of 1311.92 feet to Survey Station 376+56.40; thence N. 68° 58' 45" E. a distance of 5014.57 feet to Survey Station 426 + 70.97, a point on the range line between Ranges 72 and 8 E., said point lying south 854.80 feet from an iron pipe marking the 2 section corner common to Section 25, T. 3 N., R. 72 E., and Section 30, T. 3 N., R. 8 E., WM.; thence continuing N. 68° 58' 45" E. a distance of 5185.91 feet to Survey Station 478 + 56.88; thence N. 84° 44' 15" E. a distance of 332.00 feet to Survey Station 481 + 88.88, a point on the section line common to Sections 29 and 30, said point lying N. 0° 17' 35" W. 1070.27 feet from an iron pipe marking the 2 section corner common to Sections 29 and 30, T. 3 N., R. 8 E.W.M.; thence continuing N. 84° 44' 15" E. a distance of 3361.12 feet to Survey Station 515 + 50.00; thence N. 88° 27' 45" E. a distance of 1549.81 feet to Survey station 530 + 99.81 back = 531 + 00.00 ahead; thence N. 88° 40' 30" E. a distance of 385.96 feet to survey station 534 + 85.96, a point on the section line common to Sections 28 and 29, said point lying N. 0° 01' 24" W. 1437.80 feet from a U.S.E.D. monument marking the 2 section corner common to Sections 28 and 29, T. 3 N., R. 8 E.W.M.; thence the section corner common to Sections 25 and 36, T. 3 N., R. 7 E., W.M.; thence the 1 section corner common to Sections 28 and 29, T. 3 N., R. 8 E.W.M.; thence continuing N. 88° 40' 30" E. a distance of 1285.96 feet to Survey Station 547 + 71.92; thence N. 89° 16' 30" E. a distance of 2828.08 feet to Survey station 576 + 00.00; thence N. 61° 31' 10" E. a distance of 1426.46 feet to Survey Station 590 + 26.46, a point on the section line common to Sections 27 and 28, said point lying S. 1° 25' 56" E. 571.08 feet and N. 89° 02' 22" E. 56.10 feet from a U. S. E. D. monument marking the witness corner to the coefficients. from a U. S. E. D. monument marking the witness corner, to the section corner common to Sections 21, 22, 27 and 28, T. 3 N., R. 8 E., W.M.; thence continuing N. 61° 31' 10" E. a distance of 353.26 feet to Survey Station 593 + 79.72 back=593 # 94.00 ahead; thence S. 89° 49' 00" E. a distance of 5638.33 feet to Survey Station 650 + 32.33 back = 650 + 60.34 ahead; thence N. 87° 23' 30" E. a-distance of 1302.86 feet to Survey Station 663 + 63.20; thence N. 80° 26' 00" E. a distance of 702.63 feet to Survey Station 670 + 65.83, a point on the North-South center line of Section 26, said point lying S. 0° 04' 18" E. 290.41 feet from an iron pipe marking the ½ section corner common to Sections 23 and 26, T. 3 N., range 8 E. W. M.; thence continuing N. 80° 26' 00" E. a distance of 2695.74 to Survey Station 697 + 61.57, a point on the section line common to Sections 23 and 24, said point lying N. 2° 34' 26" E. 167.09 feet from an iron pipe marking the section corner common to Sections 23, 24, 25 and 26, T. 3 N., R. 8 E. W.M.; thence continuing N. 80° 26' 00" E. a distance of 5300.73 feet to Survey Station 750 + 62.30, a point on the range line between R nges 8 and 9 E., said point lying N. 1° 18' 49" E. 1165.45 feet from an iron pipe marking the section corner common to Sections 24 and 25, T. 3 N., R. 8 E., and Sections 19 and 30, T. 3 N., R. 9 E., W.M.; thence continuing N. 80° 26' 00" .E. a distance of 5202.52 feet to Survey Station 802 + 64.82, a point on the section line common to Sections 19 and 20, said point lying south 640.81 feet from an iron pipe marking the ½ section corner common to Sections 19 and 20, T. 3 N., R. 9 E., WM.; thence continuing N. 80° 26' 00" E. a distance of 5407.30 feet to Survey Station 856 + 72.12, a point on the section line common to Sections 20 and 21, said point lying north 327.89 feet from an iron pipe marking the $\frac{1}{4}$ section corner common to Sections 20 and 21, T. 3 N., R. 9 E., WM.; thence continuing N. 80° 26'00".E. a distance of 3089.28 feet to Survey Station 887 + 61.40; thence N. 70° 33' 00" E. a distance of 2354.40 feet to Survey Station 911 + 15.80, a point on the Section line common to sections 21 and 22, said point lying S. 2° 20' 00" E. 854.79 feet from an iron pipe marking the section corner common to Sections 15, 16,