

SCHEDULE "A" - DESCRIPTION OF EQUIPMENT (continued)

anox 41 mg 75

Item No.	Unit No.	Type and Description
9	9	Trimmer

One (1) 2h' Prescott-Portland 13-saw model PT200 selective trimmer with mechanical lift saw ladders, steel bridge and frame, 13 chain steel frame feed table 10' long with 5 end-aligning dead rolls, lifts removed from 2 end saws, cables to fingerboard control; 30 H.P., 865 R.P.M., 220/hh0 V. Allis Chalmers induction motor saw and lift drive with manual starting compensator and 22' of 12" conduit wiring; 5 H.P., 100 R.P.M. Falk Motoreducar feed drive with Louis-Allie 220/hh0 V. motor.

10 10 Rolls and Transfer, Behind Transfer

Train of nine (9) 10x2h" pipe rolls with 1 11/16" ball bearing boxes set in 30° long steel roll case with 8° channel iron stringers, 3½° high 2° timber fence one side, 1° roller chain roll drives from Foote worm gear reducer with V-belt drive by 3 H.P. motor.

One (1) 19' wide by 6' long 7-chain receiving transfer table after rolls, #78 Reof Top chain on channel chainways with formed tail drums, metal clad wood dock on timber frame, 8" head sprockets on 1 15/16" shaft with ball bearings, roller chain drive from tail shaft of next transfer.

11 11 Green Chain Transfer

Green sorting transfer table with 21' wide by 32' long 5-chain incline transfer table to green chain.

12 12 Edger

One (1) 28" single fixed saw edger for re-mill.

One (1) 16"x42" belt conveyor from edger to transfers to trimmer.

PAGE & OF 28 PAGES