thence southerly 197 feet, more or less, parallel with said east line of Parcel 2 to a point on the north right of way line of said East Douglas Street 25 feet east of the southeast corner of said Parcel 2 when measured along the north right of way line of said East Douglas Street; thence westerly 25 feet along said north right of way line to the southeast corner of said Parcel 2; thence northerly along the east lines of said Parcels I and 2 to the point of beginning.

C-248-Blalock Substation

In GILLIAM County, State of OREGON:

C-248 Hem: A tract of land described as follows:

Beginning at a point 1667,40 feet west and 255,57 feet north of the southeast corner of Section 7 in Township 2 North, Range 20 East of the Willamette Meridian; thence north 200 feet to an iron pipe; thence west 200 feet to an iron pipe; thence south 200 feet to an iron pipe; thence east 200 feet to the point of beginning which point is located by an iron pipe.

C-249-Willow Creek Substation

In GILLIAM County, State of OREGON:

C-249 Item: A tract of land described as follows:

Commencing at a point south 70° 44′ east 2490.41 feet from the west quarter corner of Section 26, Township 3 North, Range 22 East of the Willamette Meridian; thence north 28° 10′ west 56.40 feet to the true point of beginning; thence north 89° 24′ east 306.61 feet; thence south 0° 36′ east 300.00 feet; thence south 89° 24′ west 150.00 feet; thence north 28° 10′ west 338.06 feet to the point of beginning.

C-250—Kane Creek Substation

In Jackson County, State of Oregon:

C-250 Hem: A tract of land described as follows:

Commencing at the northwest corner of Donation Land Claim No. 37, Township 36 South, Range 3 West, of the Willamette Meridian; thence south 0° 10′ west a distance of 536.78 feet; thence south 89° 50′ east 20.00 feet to the true point of beginning; thence south 89° 50′ east 227.00 feet; thence north 0° 10′ east 340.28 feet; thence south 62° 45′ west 255.72 feet; thence south 0° 10′ west 222.53 feet to the true point of beginning.