

SCHEDULE "A" - DESCRIPTION OF EQUIPMENT
(continued)

One (1) Hydraulic barker installation, built 1956, with major components as follows (continued)

One (1) Vickers T90A hydraulic power pack unit for log haul drive, assembled on a 90-gallon reservoir; complete with 30 H.P., 1200 R.P.M., 220/440 V. General Electric motor #ON8280824 and 2 H.P., 1200 R.P.M., 220/440 V. Wagner motor #AAK3R.

One (1) Train of 9 - 12x36" chain driven ribbed pipe rolls on 42' long steel roll case, discharge from log haul, roller chain and V-belt drive through worm gear reducer by $7\frac{1}{2}$ H.P., 1800 R.P.M., 220/440 V. Brooks induction motor #284-G26575; five arm log kicker set in roll case for discharging peeled logs to pond, air operated.

One (1) Refuse conveyor from under rolls to barker hopper conveyor, #78 chain and flights, worm gear and motor drive.

One (1) Winch unit set alongside roll case, shop assembled with Tulsa winch (truck mounting power take-off type) roller chain drive from twin cylinder Scule steam feed works Engine, air operated.

One (1) Intake screen and float in pond of typical Hansel design, 20' of low pressure flexible hose from screen unit to pipeline to supply and main pumps, high pressure piping from pump to barker.

Spare parts for barker, standard inventory as recommended by Hansel Engineering Co.

One (1) 440 V. power panel with open pole line from transformer setting and 3" conduit wired lead-in; 1 - 400 A., 2 - 200A. and 12 - 30 to 100 A. safety switches; 8 size 1, 2 size 2 and 1 size 3 magnetic starters, 1 size 3 combination type magnetic starter, CR7008.

One (1) 36" Diameter by 8' long rotary drum screen for screening bark out of water from bottom hopper conveyor, V-belt drive by 2 H.P., 1800 R.P.M. U.S. motor.

One (1) 20' Steel trough conveyor from rotary screen to bark conveyor with #78 chain and drag flights, 12x8" formed trough, return trough, worm gear reducer and motor drive.

One (1) 48" Diameter Sweco separator screen for effluent bark lines.