

93217 LAND CORNER RECORD

SKAMANIA

County

T. 7 N. R. 5 E. W. 1.

Corner Code No. E-17.

Segregated Surveys:

Name: SOUTH WEST CORNER SECTION 2

Corner No.:

DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Town site

1. History of Corner Establishment and Subsequent Restoration:

CORNER ORIGINALLY SET BY GOVERNMENT LAND OFFICE SURVEY
THAT IN THE NOTES WAS ORIGINALLY A POST

2. Description of Evidence Found:

BTs 1 1/2" GALV I.P. 10X12X10 STONE w/iron marks
23" SILVER FIR STUMP S84 3/4 E 50.82 VISIBLE SCRIBE
30" " " N21 3/4 E 396 NO MARKS
23" " " PUSHED OVER FACE BURIED N78W 759
36" " " " S11 3/4 W 40.26
WEY CO RP
6" SILVER FIR N44W 570' WEY CO. TAG

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 161. Page No. 16 Date of work 9-27-81

SET a 2 1/2 X 30" PIPE
WITH A BRASS CAP
26" in THE GROUND
MARKED

T7N R5E

S31 S2

S101 S11

1981

LS15652

SCRIBED
T7N R5E
S3 BT

BT

N43 3/4 W 741
11.146 MILESS82W 13.39
5" SILVER FIRBT
T7N R5E
S10 BTSCRIBED
X BT

BT

N40E 12.50
5" SILVER FIRSIDE 5.65
8" SILVER FIRBT
SCRIBED
T7N R5E
S11 BTUSFS 54-3 SIGNS ON
54-4 ALL BTs6" RED BAND PAINTED
AROUND ALL BTs

DISTANCES TAKEN HORIZ FROM
MONUMENT TO BRASS SURVEY
TAGS LS15652 NAILED IN TOP
CIRCLE OF NEWLY SCRIBED B

Washington Plane Coordinates: Zone, Y, X, X
Order Accuracy: Derived From: 1/2 inch


Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date October 10, 1981

Signature Michael A. Hobbs Certificate No. LS 15652

[SEAL]



93217

AUDITOR'S CERTIFICATE

Filed for record this 22nd day of October 1981 at 11:00 A.M. In Book 7/5 of Monuments at page 5 at the request of Hobbs & Assoc.

Seal Messenger by B. Babcock
County Auditor