

93408

LAND CORNER RECORD

SKAMANIA

T. 7 N, R. 5 E, W.M.
Segregated Surveys:County
Corner Code No. C-17

Name: WEST 1/4 CORNER SECTION 2

Corner No.: W 1/4-52

D.L.C., H.E.S., Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

CORNER ORIGINALLY SET BY GOVERNMENT LAND OFFICE SURVEY

RESTORED BY LONG BELL TIMBER COMPANY 1947

THEIR NOTES SHOW - 2 BT'S

40" WHITE FIR S82 1/2 E 30.80'

36" " " N17 W 17.80'

2. Description of Evidence Found:

2 BT'S 40" WHITE FIR STUMP S78 E - 33.00' - VISIBLE KNIFE SCRIBE

NOTE: SLOPE DISTANCE AND WRONG QUADRANT

36" WHITE FIR STUMP N20 W 17.82' - VISIBLE KNIFE SCRIBE

NOTE: DISTANCE TAKEN TO FACE

BY USING THIS COMBINATION - MATCHES AS CLOSE TO ORIGINAL NOTES AS CAN BE RESTORED

THIS LOCATION ALSO MATCHES LINE CALL 120' SOUTH TO TOP OF ASCENT

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No.

161-1 Page No. 1 Date of work 10-23-81

SET A 2 1/2" X 30" PIPE - 26" IN THE GROUND
WITH A BRASS CAP MARKED
T7N R5E1/4 MEASUREMENTS TAKEN HORIZ. FROM MONUMENT TO
S31/52 BRASS SURVEY TAGS LS15652 NAILED IN TOP CIRCLE
1981 OF NEWLY SCRIBED BT'S

LS15652

USFS 5413 SIGNS ON ALL BT'S
54146" PAINTED RED
BAND ON ALL
BT'S

SCRIBED

1/4 S3 BT BT

S57W 23.00'
10" SILVER FIRS53E 10.68'
6" SILVER FIRBT.
SCRIBED
1/4 S2 BT

Washington Plane Coordinates: Zone, Y, X

Order Accuracy. Derived From:

Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date November 23, 1981

Signature

Michael G. Hobbs

Certificate No.

LS15652

AUDITOR'S CERTIFICATE

Filed for record this 3rd day of December 1981 at 12:40 P.M. In
Book 7/5 of Monuments at page 14 at the request of

Michael G. Hobbs

D.M. Olson
County Auditor