


LAND CORNER RECORD

T. 7 N, R. 5E W.M. County SKAMANIA
Segregated Surveys: Corner Code No. P-9
Name: EAST 1/4 CORNER SECTION 20 Corner No.:
DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:
CORNER ORIGINALLY SET BY GOVERNMENT LAND OFFICE SURVEY

2. Description of Evidence Found:

5/8" REBAR - 20" LONG - 2" OUT OF GROUND
BT'S
26" FIR N7DE 24.42 VISIBLE SCRIBE USFS 54-3 SIGN
10" FIR STUB S58 1/4 W 20.46' VISIBLE SCRIBE USFS 54-3 SIGN



3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 161-1 Page No. 18 Date of work 11-25-81

SCRIBED K USFS 54-3 AND
14520 BT 54-4 SIGNS

BT

SET A 2 1/2 X 30" GALV.
PIPE 26" IN THE GROUND
WITH A BRASS CAP
MARKED

T9N R5E
1/4
S20 1/2 S21
1981
LS15652

1/84 W 49.31'
34" HEMLOCK

DISTANCE TAKEN HORZ FROM
MONUMENT TO BRASS SURVEY
TAG LS15652 NAILED IN TOP
CIRCLE OF NEWLY SCRIBED "B"

PAINTED 6" RED BAND AROUND ALL BT'S

Washington Plane Coordinates: _____ Zone, Y _____, X _____

Order Accuracy. Derived From: _____

Pin Pointed on Photo No. _____ Date _____ Located at _____

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date November 30, 1981
Michael G. Plabbe LS15652
Signature _____ Certificate No. _____

[SEAL]

AUDITOR'S CERTIFICATE

Filed for record this 3rd day of December 1981 at 12:45 P.M. In
Book 7/5 of Monuments at page 15 at the request of
Michael G. Plabbe
G.M. Olson
County Auditor