

# LAND CORNER RECORD

T. 4 N, R. 7E, W.M. Skamania County  
Segregated Surveys: Corner Code No. G-13

Name: One-quarter corner Corner No.:  
DL, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

### 1. History of Corner Establishment and Subsequent Restoration:

Corner originally established by Deputy Jacob Richardson under Contract No. 459 in July/Aug. 1895.  
Set post  
Scribed 12" Fir N50E-26 lks..  
6" Maple N70W-12 lks..

### 2. Description of Evidence Found:

No evidence of the original corner or PT's found during a thorough search of the area indicated. Corner set at proportion position.

### 3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. \_\_\_\_\_ Page No. \_\_\_\_\_ Date of work 5/12

Set 2 1/2"x30" Gal steel pipe with a 2 1/2" Brass cap in a mound of stone. Marked:  
New Bearing Trees:

- 9" D-Fir N45E, 11.1 ft. scribed MS40 upper blaze and a lower blaze scribed BT and with a 3/4" Brass disk stamped PLS 16337.
- 1" Hemlock S27W, 25.6 ft. scribed MS9 upper blaze and a lower blaze scribed BT and with a 3/4" Brass disk stamped PLS 16337.


T.4N R.7E

S9 | S10

1982

PLS 16337

Set guard post west with sig 54-4 and BM 102 decal.  
Nailed 54-4 and BT signs to PT's and painted band and blazes red.



Washington Plane Coordinates: \_\_\_\_\_ Zone, Y. \_\_\_\_\_, X. \_\_\_\_\_  
Order Accuracy. Derived From: \_\_\_\_\_

Pin Pointed on Photo No. \_\_\_\_\_ Date \_\_\_\_\_ Located at \_\_\_\_\_

### SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date 5.12.82

Signature \_\_\_\_\_

Certificate No. \_\_\_\_\_



### AUDITOR'S CERTIFICATE

Filed for record this \_\_\_\_\_ day of \_\_\_\_\_ 1982 at \_\_\_\_\_ M. In Book \_\_\_\_\_ of \_\_\_\_\_ at page \_\_\_\_\_ at the request of \_\_\_\_\_

County Auditor

# LAND CORNER RECORD

T. 4 N, R. 7E, W.M. Shamania County  
Segregated Surveys: Corner Code No. G-13

Name: One-quarter corner Corner No.:  
DLC, HES, Tract Mining Claim, Indian Allotment, Federal Reserve, Townsite.


1. History of Corner Establishment and Subsequent Restoration:  
Corner originally established by Deputy Jacob Richardson under Contract No. 459 in July/Aug. 1895.  
Set post  
Scribed 1 1/2" Fir N50E-26 lks..  
6" Maple N'0W-43 lks..

2. Description of Evidence Found:  
No evidence of the original corner or PT's found during a thorough search of the area indicated. Corner set at proportion position.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 5 Page No. Date of work 5/82

Set 2 1/2"x30" Gal steel pipe with a 2" Brass cap in a mound of stone. Marked:  
New Bearing Trees:  
9" D-Fir N45E, 11.1 ft. scribed N510 upper blaze and a lower blaze scribed BT and with a 3/4" Brass disk stamped PLS 1633.  
1 1/2" Hemlock S27W, 25.5 ft. scribed N59 upper blaze and a lower blaze scribed BT and with a 3/4" Brass disk stamped .LS 1633.  
Set guard post west with sign 54-4 and BM 102 decal.  
Nailed 54-4 and BT signs to PT's and painted band and blazes red.

T.4N R.7E  
S9 | S10  
1982  
PLS 1633



Washington Plane Coordinates: Zone, Y, X  
Order Accuracy. Derived From:  
Pin Pointed on Photo No. Date Located at

### SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date 5.15.82  
Signature \_\_\_\_\_ Certificate No. \_\_\_\_\_



### AUDITOR'S CERTIFICATE

Filed for record this \_\_\_\_\_ day of \_\_\_\_\_ 1982 at \_\_\_\_\_ M. In Book \_\_\_\_\_ of \_\_\_\_\_ at page \_\_\_\_\_ at the request of \_\_\_\_\_  
County Auditor