

LAND CORNER RECORD

Skamania

County

T 4 N. R 7E W.M.

Corner Code No. G-1.

Segregated Surveys:

Name: One-quarter corner

Corner No.:

BLM, BLS, T, et. Major Class, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:
 Corner originally established by Deputy Jacob Richardson under Contract No. 459 in July/Aug. 1895.
 Set post
 Scribed 10" Fir 39°E-50 lks..
 5" Dogwood N45°W-36 lks..

2. Description of Evidence Found:

No evidence of the original corner or its accessories found. Falls on blazed line extended from the North.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 5 Page No. 16 Date of work 4/72

Set 2 1/2"x30" Aluminum pipe with a 2" Aluminum cap. Marked:

New Bearing Trees:

10" Hemlock 350w, 11.2 ft. scribed S10 upper blaze and a lower blaze scribed BT and with a 3/4" Brass disk stamped HCS 1-237.

5" D-Fir 310z, 20.2 ft. scribed S11 upper blaze and a lower blaze scribed BT and with a 3/4" Brass disk stamped PLS 16337.

Set guard post North with sign 54-4 only.

Nailed 54-4 and BT signs to BT's and painted band and blazes red.

T. 4N R. 7E
S10 | S11
13 2
PLS 16337

Washington Plane Coordinates: Zone Y
Order Accuracy. Derived From: X

Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in accordance with the provisions of Chapter 50, Laws of 1973. Date

Signature

Certificate No.



AUDITOR'S CERTIFICATE

Filed for record this day of 1972 at M. In Book of at page at the request of

County Auditor

Form prescribed by Bureau of Surveys and Maps pursuant to the provisions of Section 5 (2), Chapter 50, Laws of 1973

ROLL 682.1
DAILY RECORDINGS
BOARD OF COUNTY COMMISSIONERS
MARKING APPLIED 10/15