

LAND CORNER RECORD

T. 4 N, R. 7E . W.M. Skamania County
Segregated Surveys: Corner Code No. N-13
Name: Section Corner Corner No.:
DLC, BPS Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

Corner originally established by Deputy Jacob Richardson under Contract No. 459 in July/Aug. 1895.

Set post

- Scribed 36" Fir N72E-59 lks.
- 18" Fir S12E-51 lks.
- 15" Cedar S30W-100 lks.
- 7" Yew N10W-50 lks.

2. Description of Evidence Found:

- U.S.D.A. 2 1/2" Brass cap on a 2" Iron pipe.
- Orig. 7" now 10" Yew NW, 33.0 ft. blaze partially healed-only old aze marks remain (record N10W).
- Orig. 36" now 44" D-Fir N72E, 45.5 ft. (to face) scribing visible on partially healed blaze.
- Orig. 18" now rotted D-Fir mound 1 ft. high S12E, 53.7 ft..
- Orig. 15" now 26" Cedar S30W, 64.5 ft. (record 65 ft.) scribing visible on open face.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 5 Page No. 3 Date of work 4/82

New Bearing trees

14" D-Fir S22E, 22.4 ft. scribed T4NR7E S22 upper blaze and a lower blaze scribed BT and with a 3/4" Brass disk stamped PLS 16337.

Nailed 54-4 and 12 signs to all BT's and painted band and blazes red.

Set guard post South with sign 54-4 only.

Marked:

T.4N	R.7E
S16	S15
S21	S22
1982	
PLS 16337	

Washington Plane Coordinates: Zone, Y, X
Order Accuracy. Derived From:

Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date 5-8-82

Signature

Certificate No.



AUDITOR'S CERTIFICATE

Filed for record this day of 19 at M. In Book of at page at the request of

County Auditor

Form prescribed by Bureau of Surveys and Maps pursuant to the provisions of Section 5 (2), Chapter 50, Laws of

ROLL 682.1
DAILY RECORDING-S
BOARD OF COUNTY COMMISSIONERS
MARKING APPLICATIONS