

LAND CORNER RECORD

Okamania County
 T. 4 N, R. 7E W.M. Corner Code No. G-10
 Segregated Surveys:
 Name: Witness Corner Corner No.:
D.L.C. RES. Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

N/A

2. Description of Evidence Found:

N/A

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 5 Page No. 17 Date of work 5/82

Set 2"x30" Aluminum pipe with a 2" Aluminum cap in a mound of stone. Marked:

New Bearing Trees:

16" D-Fir NW, 37.5 ft. square blaze chest high scribed "X" and two lower blazes the upper one scribed CE1/1639 and the lower scribed ET and with a 3/4" Brass disk stamped HS 16337.

T.4N R.7E
 WC
 W1/16
 C—C
 39

11" West stem of double D-Fir SW, 17.4 ft. square blaze chest high scribed "X" and a lower blaze scribed ET and with a 3/4" Brass disk stamped HS 16337.

1982 HS 16337

Set guard post North with sign 54-9 and EX 102 decal. Nailed 54-9 and ET signs to ET's and painted band and blazes red.

Note: Corner falls in pavement of N-54 set witness corner North on line 47.76 ft. from concrete nail at corner point.

Washington Plane Coordinates: Zone, Y
 Order Accuracy. Derived From:

Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date 5/21/82

Signature *James W. Bishop*

Certificate No. 16337



AUDITOR'S CERTIFICATE

Filed for record this day of 19 at M. In Book of at page at the request of

County Auditor