

LAND CORNER RECORD

Skamania

County

T. 4 N, R. 7E, W.M.

Corner Code No. E-15

Segregated Surveys:

Name: One-quarter corner

Corner No.:

DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

Corner originally established by Deputy Jacob Richardson under Contract No. 459 in July/Aug. 1895.

Set post

Scribed 6" Hemlock N70W, 27 lks..

12" Hemlock S18E, 53 lks..

2. Description of Evidence Found:

No evidence of the original corner or its accessories exist. Corner falls in a recent clearcut. Set corner on line 0.20 chains East of creek and 5 chains West of creek.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 5 Page No. 3 Date of work 4/82

Set 2 1/2"x30" Gal. steel pipe with a 2 1/2" brass cap in a mound of stone. Marked:

Drove R/k spike in center of 30" Hemlock stump N60W, 13.0 ft..

T.4N R.7E

Chisled "XBO" on top of 3"x4" boulder S20E, 10.2 ft..

S3

Set guard post North with sign 54-4 only.

S10

Nailed BT and 54-4 sign to Hemlock stump.

1982

PLS 16337

Washington Plane Coordinates: Zone, Y, X

Order Accuracy. Derived From:

Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date 4/22/82

Signature

Certificate No.



AUDITOR'S CERTIFICATE

Filed for record this day of 1982 at M. In Book of at page at the request of

County Auditor

Form prescribed by Bureau of Surveys and Maps pursuant to the provisions of Section 5 (2), Chapter 50, Laws of 1973.

ROLL 682.1
DAILY RECORDING
BOARD OF COUNTY COMMISSIONERS
MANAGING APPLICATIONS