

LAND CORNER RECORD

Skamania County
 T. 4 N. R. 7E W.M. Corner Code No. J-13
 Segregated Surveys: Name: Section Corner Corner No.:
 DLC. HES Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:
 Corner originally established by Deputy Jacob Richardson under Contract No. 459 in July/Aug. 1895.
 Set post
 Scriberd 12" Cedar N10E-5 lks..
 18" Hemlock S30E-43 lks..
 24" Hemlock S65W-36 lks..
 12" Hemlock N68W-34 lks..

2. Description of Evidence Found:
 None

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 5 Page No. 12 Date of work 4/82

Set 2"x30" Aluminum pipe with a 2" Aluminum cap. Marked:
 Drove R/R spike in crack in rock ledge N37W, 24.7 ft.. T.4N R.7E
 Drove R/R spike in crack in rock ledge N57E, 13.7 ft.. S9 S10
 NW corner foundation of residence S1E, 41.0 ft.. S16 S15
 SE corner foundation of garage, S40W, 14.2 ft.. 1982
 No guard post set at owners request. PLS 16337
 No PI's marked or paint used for same reason.

Corner point is .30 chains South of the edge of Wind River as measured from a rock ledge and 3.00 chains East of Spring Creek.
 This position was discussed with PLS 15731 representing Birkenfeld and PLS 15673 representing Longview Fibre Corp. on 4-30-82. They were in agreement that this position is superior to proportion.

Washington Plane Coordinates: Zone Y, X
 Order Accuracy. Derived From:
 Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date 4/82

Signature

Certificate No. 2442



AUDITOR'S CERTIFICATE

Filed for record this 12th day of April 1982 at 11:00 A.M. In Book of at page at the request of

County Auditor