

LAND CORNER RECORD

Skamania

County

T 7 N, R 6E, W.M.

Corner Code No. V-17

Segregated Surveys:

Name: Section Corner

Corner No.:

DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

This corner was originally set by Deputy Lewis D.W. Shelton in July 1899, & Oct.-Dec. 1900 under Contract No. 552.

Remonumented by Floyd A. Brooks, Cadastral Surveyor in Oct. & Nov. 1961.

Set Fir post.

Set concrete post with Brass cap.
Scribed 20" Fir N9E-90½ lks..

- Scribed 12" Fir N54½E-39 lks..
- 12" Fir S40E-29½ lks..
- 4" Fir S65½W-52 lks..
- 12" Fir N52½W-36 lks..

2. Description of Evidence Found:

- 2½" B.L.M. Brass cap on 4"x4" Concrete post.
- Orig. 12" now 25" D-Fir stump N54½E, 25.7 ft..
- Orig. 12" now 30" D-Fir S40E, 19.5 ft. blaze grown over.
- Orig. 4" now 24" D-Fir S65½W, 34.3 ft. blaze grown over.
- Orig. 12" now 36" D-Fir N52½W, 23.8 ft. blaze grown over.
- Brooks 20" Fir N9E-90½ lks., blaze grown over.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 2 Page No. 2 Date of work 6/22

Set guard posts North and East with signs 54-4 and BX 102 decals.
Painted red band and blazes red on BT's
Nailed signs 54-4 and BX signs on BT's.



Washington Plane Coordinates: Zone, Y, X
Order Accuracy. Derived From:

Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date

Signature *Lloyd D. Brooks* Certificate No. 16337



AUDITOR'S CERTIFICATE

Filed for record this 7th day of JULY 1982 at 11:30 A.M. In Book 7/6 of RECORDS at page 7 at the request of

BISBOP SURVEYING INC

J.M. Wilson

County Auditor