

LAND CORNER RECORD

Skamania

County

T 7 N, R 6E, W.M.

Corner Code No. P-13

Segregated Surveys:

Name: One-quarter Corner

Corner No.:

DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

This corner was originally set by Deputy Lewis D.W. Shelton in July 1900, & Oct.-Dec. 1900 under Contract No. 552.

Remonumented by Floyd A. Brooks, Cadastral Surveyor in Oct. & Nov. 1961.

Set Cedar post.

Set Iron post with Brass cap.

Scribed 16" Fir N89E-12 lks..

Scribed 16" Fir N66E-44 lks..

12" Fir S65 1/4 W-13 lks..

9" Hemlock S35 1/4 W-32 1/2 lks

2. Description of Evidence Found:

BLM 2 1/2" Iron post with Brass cap.

Orig. 16" now 18" D-Fir snag N89E-12 lks. scribing visible on opened blaze.

Brooks 16" now 18" D-Fir N66E-44 lks. healed blaze.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 2 Page No. 13 Date of work June 1982

New Bearing Trees:

12" Hemlock N33W, 64.5 ft. scribed 1/2" S21 upper blaze and a lower blaze scribed BT and with a 3/4" Brass disk stamped PLS 16337.

Set guard post South with sign 54-4 and BM 102 decal.

Nailed 54-4 and BT signs to BT's and painted band and blazes red.



Washington Plane Coordinates: Zone, Y, X

Order Accuracy. Derived From:

Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date

Signature *Larry D. Miller*

Certificate No. 16337



AUDITOR'S CERTIFICATE

Filed for record this 13th day of JULY 1982 at 12:00 P.M. In Book 7/6 of RECORDS at page 12 at the request of

BISAC SURVEYING INC

J. M. Owen

County Auditor