

LAND CORNER RECORD

Skamania

County

T. 7 N, R. 6E, W.M.

Corner Code No. C-17

Segregated Surveys:

Name: One-quarter corner

Corner No.:

DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

This corner was originally set by Deputy Lewis D.M. Shelton in July 1899, & Oct.-Dec. 1900 under Contract No. 552.

Remonumented by Floyd A. Brooks, Cadastral Surveyor in Oct. & Nov. 1961.

Set Cedar post.

Set Iron post with Brass cap.

Scribed 12" Fir N15E-15 lks..

Scribed 10" Hemlock S47E-30 1/2 lks..

6" Cedar N70W-26 lks..

10" Cedar N57W-38 lks..

2. Description of Evidence Found:

BLM Iron post with Brass cap.

Orig. 12" now 15" D-Fir snag N15E-1 1/4 lks.-marks rotted away from open blaze.

Brooks 10" Cedar now 1 1/4" N57W-3 lks. scribing visible on partially healed blaze.

Brooks 10" now 11" down Hemlock stood S47E-30 1/2 lks. scribing visible.


3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 2 Page No. 17 Date of work July 1982

New Bearing Tree:

15" Hemlock S51E, 11.6 ft. scribed 132 upper blaze and a lower blaze scribed BT and with a 3/4" Brass disk stamped PLS 1882.

Set guard post North with sign 54-4.

Nailed 54-4 and BT signs to BT's and painted band and blazes red.



Washington Plane Coordinates: Zone, Y, X

Order Accuracy. Derived From:

Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date July 20, 1982

Signature Larry D. Bishop

Certificate No. 16337



AUDITOR'S CERTIFICATE

Filed for record this 14 day of Sept. 1982 at 1:30 P.M. In Book 716 of Monument at page 32 at the request of

Signature Larry M. Olson
County Auditor