

94754

LAND CORNER RECORD

T. 7 N, R. 6E, W.M. Skamania County Corner Code No. G-21

Segregated Surveys: Name: One-quarter corner Corner No.:
DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

This corner was originally set by Deputy Lewis D.W. Shelton in July 1899, & Oct.-Dec. 1900 under Contract No. 552.

Remonumented by Floyd A. Brooks, Cadastral Surveyor in Oct. & Nov. 1961.

Set Cedar post.

Set Iron post with Brass cap.

Scribed 18" Wh.Fir S86E-41 lks..
14" Wh.Fir N65W-25 lks..

Scribed 8" Hemlock S73E-41½ lks..
11" Hemlock N44½W-11½ lks..

2. Description of Evidence Found:

BIM Iron post with Brass cap and a 1" Iron pipe.
Orig. 14" now 18" rotted Wh.Fir stub N65W-25 lks.- no marks remain.
Brooks 8" now 9" Hemlock S73E-41½ lks.-healed blaze.
Brooks 11" now 13" Hemlock N44½W-11½ lks.-healed blaze.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 6 Page No. 15 Date of work Aug. 1982

Nailed 54-4 and BT signs to BT's and painted band and blazes red.
Set guard post North with sign 54-4 only.

Washington Plane Coordinates: Zone, Y, X
Order Accuracy. Derived From:

Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date 8/27/82

Signature Larry D. Bishop Certificate No. 16337



AUDITOR'S CERTIFICATE

Filed for record this 14 day of Sept 1982 at 1:30 P. M. In Book 7-6 of monuments at page 42 at the request of

Signature Guy M. Brown County Auditor

Printed by Bureau of Surveys and Maps pursuant to the provisions of Section 5 (2), Chapter 50, Laws of 1973.