

94758

LAND CORNER RECORD

T. 7 N, R. 6E, W.M. Skamania County
Segregated Surveys: Corner Code No. C-25

Name: One-quarter corner Corner No.:
DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

This corner was originally set by Deputy Lewis D.W. Shelton in July 1899, & Oct.-Dec. 1900 under Contract No. 552. Remonumented by Floyd A. Brooks, Cadastral Surveyor in Oct. & Nov. 1961.
Set Hemlock post. Set Iron post with Brass cap.
Scribed 50" Fir S42E-24 lks.. Scribed 10" Fir N35E-31 lks..
36" Cedar S623/4W-41 lks.. 13" Fir N21W-42½ lks..

2. Description of Evidence Found:

BLM 3" Brass cap on 2½" Iron post.
Orig. 50" now 72" down D-Fir S42E-24 lks.-scribing visible.
Orig. 36" now 50" Cedar stump no marks S63E-41 lks..

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 9 Page No. 14 Date of work Aug. 1982

New Bearing Trees:

22" Wh.Fir N81W, 68.5 ft. scribed ¼S1 upper blaze and a lower blaze scribed BT and with a ¾" Brass disk stamped PLS 16337.
11" Hemlock N19E, 23.6 ft. scribed ¼S6 upper blaze and a lower blaze scribed BT and with a ¾" Brass disk stamped PLS 16337.
Nailed signs 54-4 and BT signs to BT's - painted red and blazes red on BT's.
Set guard post with sign 54-4 and BM 102^{mm} decal South.

Washington Plane Coordinates: Zone, Y, X
Order Accuracy. Derived From:
Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date 8/27/82
Signature *Jerry D. Bishop* Certificate No. 16337

[SEAL]



AUDITOR'S CERTIFICATE

Filed for record this 14 day of Sept. 1982 at 1:24 P.M. In Bock 7/6 of Monumental at page 46 at the request of Jerry D. Bishop
Jerry D. Bishop
County Auditor