

94770

LAND CORNER RECORD

Shumania County
T. 21 N, R. 6E, W.M. Corner Code No. L-21
Segregated Surveys:

Name: One-quarter corner Corner No.:
DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

This corner was originally set by Deputy Lewis D.W. Shelton in July 1899, & Oct.-Dec. 1900 under Contract No. 552.
Set Cedar post
Scribed 12" Cedar S41E-1/4 lks.
12" Hemlock N60,12-30 lks.
Monumented by Floyd A. Brooks Cadastral Surveyor in Oct. & Nov. 1964.
Set 2 1/2" Iron Post with a Brass Cap
Scribed 6" W. Mir N82E-10 1/2 lks.
6" W. Mir N49 1/2-46 lks.

2. Description of Evidence Found:

MIN 2 1/2" iron post with a brass cap
Orig. 12" now 20" Cedar 9' high stump- scribing visible- S41E-1/4 lks.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. Page No. Date of work

New Bearing trees:
10" hemlock N65.1 100.2 ft. scribed, 3/4" upper blaze and a lower blaze scribed 57 and with a 3/4" brass disk stamped FAS 16337.
2" Noble Fir 355.3 ft. scribed 1343 upper blaze and a lower blaze scribed 57 and with a 3/4" brass disk stamped FAS 16337.

Set guard post South with sign 54-4.
Nailed 54-4 and 14 signs to 54-3 and painted band and blazes red.



Washington Plane Coordinates: Zone, Y, X
Order Accuracy. Derived From:
Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date 11/22/1982
Signature Larry D. Bishop Certificate No. 16337



AUDITOR'S CERTIFICATE

Filed for record this 14 day of Sept 1982 at 1:30 P. M. In Book 76 of Monuments at page 58 at the request of Larry D. Bishop
County Auditor