

LAND CORNER RECORD

T 3 N, R 8 East, W.M. Skamania County
 Segregated Surveys: Corner Code No. E-7
 Name: n/a Corner No.: n/a
 DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

Originally set by G.L.O. surveyor, Robert A. Webster, in 1896.
 An iron pipe with stamped brass cap set by Skamania County Engineers.
 Corner is shown on surveys recorded in Book 1 pages 118, 260, and 261; and Book 2 page 21.

2. Description of Evidence Found:

18" Fir B.T. stump with visible scribe at N 65 E, 19.7 feet.
 15" Fir B.T. stump and log with visible scribe at S 77 E, 19.5 feet.
 Above described Skamania County iron pipe.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 600.22 Page No. 56 Date of work 11-18-82

Shown on D.N.R. Final Map #462.

See corner diagram on reverse side.

Washington Plane Coordinates: South Zone, Y 161,250.81 X 1,662,088.29
 3rd Order Accuracy. Derived From: 1975 Olson Eng. survey data at S.W.
 corner Sec. 5 (Recorded in Bk 1 page 54, Records of Skamania County)
 Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date Sept. 29, 1983

Signature

11977

Certificate No.

AUDITOR'S CERTIFICATE

Filed for record this 4th day of OCTOBER 1983 at 1:00 P.M. In Book 3/8 of MONUMENTS at page 56 at the request of Washington State Department of Natural Resources

E.M. Olson Jr. & Sons, Dep.
 County Auditor

Form prescribed by Bureau of Surveys and Maps pursuant to the provisions of Section 5 (2), Chapter 50, Laws of 1973.



GLO Survey of 1896

East on a true line, on provisional base ---

40.00 Set a post ---

15" Fir N65 1/2 E 30 L 19.80'

12" Fir S77 E 30 L 19.80'

1/4 corner S. 5 S. 8 T3N R8E

FOUND SKAMANIA CO. ENGRS

Pipe & BRASS CAP

18" Fir STUMP N65 E 19.7' TO FACE

WAVE MARKS ON BOTTOM OF FACE, CUT OFF

BELOW SCRIBE, "P" SCRIBED ON LOG LYING

NEXT TO STUMP

15" Fir STUMP S77 E 19.5' TO FACE

CUT BELOW SCRIBE "1/4 S BT." SCRIBED ON LOG

LYING NEXT TO STUMP

Other recorded surveys using this corner position:

book 1 pg 118

book 2 pg 21

book 1 pg 261

book 1 pg 260

Corner is true sta. 160

11-18-82

GORDON
BRASSLER

S. 6
600.22

