

LAND CORNER RECORD

Skamania County
 T. 3 N, R. 8 East, W.M. Corner Code No. C-5
 Segregated Surveys:
 Name: n/a Corner No.: n/a
 DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite

1. History of Corner Establishment and Subsequent Restoration:

Originally set by G.L.O. surveyor, Robert A. Webster, in 1896.
 No restoration found.

2. Description of Evidence Found:

54" Fir B.T. stump at N 79 E, 10.56 feet from corner position.
 Fits creek call to south.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 600.22 Page No. 54 Date of work 6-6-83

Shown on D.N.R. Final Map #462. See corner diagram on reverse side.

On 6-6-83, the D.N.R. set a standard D.N.R. concrete monument with stamped brass cap at position of G.L.O. bearing & distance from found B.T.

Washington Plane Coordinates: South Zone, Y 163,948.46, X 1,659,480.52
 3rd Order Accuracy. Derived From: 1975 Olson Eng. survey data at S.W.
 corner Sec. 5 (Recorded in Bk 1 page 54, Records of Skamania County)
 Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date Sept 29, 1983
 Signature M. A. Kinnaman Certificate No. 11977



AUDITOR'S CERTIFICATE

Filed for record this 6th day of OCTOBER 1983 at 1:15 P.M. In Book 3/8 of MONUMENTS at page 62 at the request of Washington State Department of Natural Resources

M. M. Olson by J. Davis, Dep
 County Auditor

WITH OVERGROWTH, FITS CREEK
CALL TO SOUTH

SET 3" CYL. CONC. MON. W/D.N.R. BRASS
CAP 5" ABOVE GROUND O.D. FROM
54" FIR STUMP (BT)