

RES 20-1808(9-77)

## LAND CORNER RECORD

Skamania County  
 T. 4 N, R. 8 East, W.M. Corner Code No. Z-9  
 Segregated Surveys:  
 Name: n/a Corner No.: n/a  
 DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

## 1. History of Corner Establishment and Subsequent Restoration:

Originally set by G.L.O. surveyor, Robert A. Webster, in 1896.  
 No restoration found.

## 2. Description of Evidence Found:

33" Fir B.T. at N 58 W, 24.63 feet from corner position.  
 37" Fir B.T. with visible scribe at N 53 E, 27.23 feet from corner position.  
 45" Fir B.T. at S 50 E, 18.64 feet from corner position.  
 35" Fir B.T. at S 41 W, 28.69 feet from corner position.

## 3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 600.22 Page No. 55 Date of work 12-2-82

Shown on D.N.R. Final Map #462. See corner diagram on reverse side.

On 12-2-82, the D.N.R. set a standard D.N.R. iron pipe with stamped brass cap at intersection of G.L.O. distances from Live B.T.'s (Distance measured from B.T. faces)

Washington Plane Coordinates: South Zone, Y 166,605.20 - X 1,664,782.50 -  
 3rd Order Accuracy. Derived From: 1975 Olson Eng. survey data at S.W.  
 corner Sec. 5 (Recorded in Bk 1 page 54, Records of Skamania County)  
 Pin Pointed on Photo No. Date Located at.

## SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date Sept 29, 1983

Signature M. A. Kinnaman Certificate No. 11977



## AUDITOR'S CERTIFICATE

Filed for record this 6th day of OCTOBER 1983 at 1:25 P.M. In Book 4/8 of MONUMENTS at page 1 at the request of Washington State Department of Natural Resources

M. M. Olson by A. Davis, Dep.  
 County Auditor

Form prescribed by Bureau of Surveys and Maps pursuant to the provisions of Section 5 (2), Chapter 50, Laws of 1973.

GLO Survey of 1896

East between S & 32

80.00 set apost ---

20" Fir N 53E 40L 26.40'

24" Fir S 50E 27L 17.82'

16" Fir S 40W 44L 29.04'

18" Fir N 56W 36L 23.76'

Section Corner <sup>22 133</sup> <sub>5 14</sub> T 34 N R 8 E

Found 4 live BT's. Cut into the  
NE BT and saw scribings. Did not  
cut into the other BT's.

No of surveys of record

Corner is trans. sta. 138

12-2-82

Laird  
Gordon  
Bressler

55  
600.22

